

# CHEM LAB RENOVATIONS | SCIENCE INNOVATION CENTER

WESTMORELAND COUNTY COMMUNITY COLLEGE  
161 COMMUNITY COLLEGE DRIVE YOUNGWOOD, WESTMORELAND COUNTY, PA, 15697



**DRAWING INDEX - VOLUME 1**

DRAWING NO	
GENERAL	
CS100	COVER SHEET
BC101	BUILDING CODE SUMMARY
ARCHITECTURAL	
A001	GEN ABBREY, SYMBOLS, AND WALL TYPES
AD101	FIRST FLOOR - DEMO PLAN
A101	FIRST FLOOR - NEW WORK PLAN
A102	ENLARGED PLAN - RM 3400 & RM 3403
A103	ENLARGED PLAN - RM 3308 & RM 3404
A104	ENLARGED PLAN - RM 3401 & RM 3402
A601	DOOR & FINISH SCHEDULE AND DETAILS
A901	ENLARGED PLANS - LAB BENCH
A902	ENLARGED PLANS - LAB BENCH
A903	FUME HOOD PLAN & ELEVATIONS
HVAC	
H000	HVAC SYMBOLS, AND ABBREVIATIONS
H101	HVAC PLAN DEMO AND NEW WORK PLANS
PLUMBING	
PD01	PLUMBING NOTES, SCHEDULES, & DETAILS
PD101	PLUMBING FIRST FLOOR DEMO PLAN
P101	PLUMBING FIRST FLOOR PLAN
ELECTRICAL	
E100	SYMBOLS, ABBREVIATIONS, AND DETAILS
E101	ELECTRICAL DEMOLITION AND NEW WORK


CHEM LAB RENOVATIONS | SCIENCE INNOVATION CENTER  
WESTMORELAND COUNTY COMMUNITY COLLEGE

1/21/2025 2:55:14 PM Autodesk Docs://004-21-01 Westmoreland CCC - Chem Lab Renovation/21-1004-01 WCCC Chem Lab Renovation CENTRAL R23.rvt



470 Washington Road, Pittsburgh, PA 15228  
412.561.7117 www.DRAWcollective.com

Contact: CHRIS BROWN  
Email: CHRISB@DRAWCOLLECTIVE.COM



**MECHANICAL ENGINEER**

ROB HERLIHY - TOWER ENGINEERING  
412-939-1743 x 140 | rherlihy@estower.com


**PLUMBING ENGINEER**

CORY WEILAND - TOWER ENGINEERING  
412-379-5368 | cweiland@tower-engineering.com

**ELECTRICAL ENGINEER**

STEFANIE BAKO - TOWER ENGINEERING  
412-939-1743 x 111 | sbako@estower.com

**TOWER ENGINEERING**  
115 EVERGREEN HEIGHTS DRIVE, SUITE 400  
PITTSBURGH, PA 15229-1346



**PROJECT / CLIENT INFO:**

PROJECT ADDRESS:  
161 COMMUNITY COLLEGE DRIVE  
YOUNGWOOD, PA, 15697

CLIENT INFO:  
WESTMORELAND COUNTY COMMUNITY COLLEGE  
145 PAVILLION LANE  
YOUNGWOOD, PA, 15697

REVISIONS

**CODE - BUILDING SUMMARY**

**BUILDING CODE ANALYSIS / SUMMARY**

**GOVERNING CODES**  
 PENNSYLVANIA UNIFORM CONSTRUCTION CODE (PA UCC)  
 INTERNATIONAL EXISTING BUILDING CODE - 2018 EDITION (IEBC-2018)  
 INTERNATIONAL BUILDING CODE - 2018 EDITION (IBC-2018)  
 INTERNATIONAL FIRE CODE - 2018 EDITION (IFC-2018) - WHERE REFERENCED  
 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - 2009 EDITION (ICC A117.1-2009)

**BUILDING / WORK AREA INFORMATION**  
**WORK AREA USE AND OCCUPANCY CLASSIFICATION:** BUSINESS GROUP B  
**TYPE OF CONSTRUCTION:** IIB  
**AUTOMATIC SPRINKLER SYSTEMS:** FULL COVERAGE IN BUILDING - NFPA 13, PER ORIGINAL 1992 DRAWINGS  
**FIRE ALARM AND DETECTION SYSTEMS:** THROUGHOUT BUILDING

**EXISTING BUILDING CODE (IBC) ANALYSIS OF ALTERATIONS:**  
 SEE PLAN THIS SHEET FOR CLASSIFICATION OF WORK AND WORK AREAS  
 NO CHANGE OF OCCUPANCY OR USE  
 NO ADDITIONS OR CHANGES TO BUILDING AREA  
 NOT A RELOCATED BUILDING

**IEBC CHAPTER CHAPTER HEADING**

**3 PROVISIONS FOR ALL COMPLIANCE METHODS**

305 ACCESSIBILITY FOR EXISTING BUILDINGS  
 305.7 ALTERATIONS AFFECTING AN AREA CONTAINING A PRIMARY FUNCTION, WHERE AN ALTERATION AFFECTS THE ACCESSIBILITY TO, OR CONTAINS AN AREA OF PRIMARY FUNCTION, THE ROUTE TO THE PRIMARY FUNCTION AREA SHALL BE ACCESSIBLE. THE ACCESSIBLE ROUTE TO THE PRIMARY FUNCTION AREA SHALL INCLUDE TOILET FACILITIES AND DRINKING FOUNTAINS SERVING THE AREA OF PRIMARY FUNCTION.  
 SEE THE PLAN FOR THE ACCESSIBLE ROUTE LOCATIONS AND THE EXISTING ACCESSIBLE TOILET AND DRINKING FOUNTAINS SERVING THE AREA OF PRIMARY FUNCTION.

403.1 REPAIRS SHALL BE DONE IN A MANNER THAT MAINTAINS THE LEVEL OF FIRE PROTECTION PROVIDED  
 404.1 REPAIRS SHALL BE DONE IN A MANNER THAT MAINTAINS THE LEVEL OF PROTECTION PROVIDED FOR THE MEANS OF EGRESS

**6 CLASSIFICATION OF WORK**

SEE PLAN FOR AREAS WITH ALTERATIONS AND CLASSIFICATION OF WORK  
 602.1 LEVEL 1 ALTERATIONS INCLUDE THE REMOVAL AND REPLACEMENT OR THE COVERING OF EXISTING MATERIALS, ELEMENTS, EQUIPMENT, OR FIXTURES USING NEW MATERIALS, ELEMENTS, EQUIPMENT, OR FIXTURES THAT SERVE THE SAME PURPOSE.  
 603.1 LEVEL 2 ALTERATIONS INCLUDE THE RECONFIGURATION OF SPACE, THE ADDITION OR ELIMINATION OF ANY DOOR OR WINDOW, THE RECONFIGURATION OR EXTENSION OF ANY SYSTEM, OR THE INSTALLATION IF ANY EQUIPMENT.  
 604.1 WORK AREA DOES NOT EXCEED 50% OF THE BUILDING AREA; NO LEVEL 3 ALTERATIONS

**7 ALTERATIONS - LEVEL 1**

702.1 ALL NEWLY INSTALLED INTERIOR WALL AND CEILING FINISHES SHALL COMPLY WITH CHAPTER 8 OF THE INTERNATIONAL BUILDING CODE.  
 703.1 ALTERATIONS SHALL BE DONE IN A MANNER THAT MAINTAINS THE LEVEL OF FIRE PROTECTION PROVIDED.  
 704.1 ALTERATIONS SHALL BE DONE IN A MANNER THAT MAINTAINS THE LEVEL OF PROTECTION PROVIDED FOR THE MEANS OF EGRESS.

**8 ALTERATIONS - LEVEL 2**

801.2 IN ADDITION TO THE REQUIREMENTS OF THIS CHAPTER, ALL WORK SHALL COMPLY WITH THE REQUIREMENTS OF CHAPTER 7.  
 802.4 THE INTERIOR FINISH OF WALLS AND CEILINGS IN EXITS AND CORRIDORS AND IN WORK AREA SHALL COMPLY WITH THE REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE.  
 803.1 THE REQUIREMENTS OF THIS SECTION SHALL BE LIMITED TO WORK AREAS IN WHICH LEVEL 2 ALTERATIONS ARE BEING PERFORMED, AND WHERE SPECIFIED THEY SHALL APPLY THROUGHOUT THE FLOOR ON WHICH THE WORK AREAS ARE LOCATED OR OTHERWISE BEYOND THE WORK AREA.  
 805.8.1 MEANS OF EGRESS IN ALL WORK AREAS SHALL BE PROVIDED WITH EXIT SIGNS IN ACCORDANCE WITH THE IBC  
 810 LEVEL 2 ALTERATIONS TO EXISTING BUILDINGS OR STRUCTURES ARE PERMITTED WITHOUT REQUIRING THE ENTIRE BUILDING OR STRUCTURE TO COMPLY WITH THE ENERGY REQUIREMENTS OF THE INTERNATIONAL ENERGY CONSERVATION CODE. THE ALTERATIONS SHALL CONFORM TO THE ENERGY REQUIREMENTS OF THE INTERNATIONAL ENERGY CONSERVATION CODE AS THEY RELATE TO NEW CONSTRUCTION ONLY.

**10 CHANGE OF OCCUPANCY**

NO CHANGE OF OCCUPANCY

**BUILDING CODE (IBC) ANALYSIS**

**IBC CHAPTER CHAPTER HEADING**

3 USE AND OCCUPANCY CLASSIFICATION  
 304.1 BUSINESS GROUP B - EDUCATIONAL OCCUPANCIES FOR STUDENTS ABOVE THE 12TH GRADE

4 SPECIAL DETAILED REQUIREMENTS BASED ON USE AND OCCUPANCY  
 HIGHER EDUCATION LABORATORIES COMPLYING WITH SECTION 428 SHALL BE PERMITTED TO EXCEED THE MAXIMUM ALLOWABLE QUANTITIES OF HAZARDOUS MATERIALS SET FORTH IN TABLES 307.1(1) AND 307.1(2) WITHOUT REQUIRING CLASSIFICATION AS A GROUP H OCCUPANCY. ENTIRE RENOVATED SUITE IS CLASSIFIED AS A SINGLE HIGHER EDUCATION LABORATORY SUITE (NO INTERNAL SEPARATIONS) AND THE QUANTITIES SET FORTH IN TABLES 307.1(1) AND 307.1(2) WILL NOT BE EXCEEDED WITHIN THE LABORATORY SUITE.  
 A HAZARDOUS MATERIALS INVENTORY STATEMENT HAS BEEN PREPARED FOR THE ANTICIPATED USE OF THE RENOVATED SUITE.

5 GENERAL BUILDING HEIGHTS AND AREAS  
 NO CHANGE TO EXISTING BUILDING HEIGHT OR AREA

**6 TYPE OF CONSTRUCTION**

TYPE IIB CONSTRUCTION  
**TABLE 601 FIRE RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS**  
 PRIMARY STRUCTURAL FRAME: 0 HRS.  
 BEARING WALLS - EXTERIOR: 0 HRS.  
 BEARING WALLS - INTERIOR: 0 HRS.  
 NONBEARING WALLS AND PARTITIONS - EXTERIOR: 0 HRS.  
 NONBEARING WALLS AND PARTITIONS - INTERIOR: 0 HRS.  
 FLOOR CONSTRUCTION AND SECONDARY MEMBERS: 0 HRS.  
 ROOF CONSTRUCTION AND SECONDARY MEMBERS: 0 HRS.

**7 FIRE AND SMOKE PROTECTION FEATURES**

707 FIRE BARRIERS  
 - AT SEPARATION OF LABORATORY AND NONLABORATORY AREAS: 1 HR.  
 - AT EXIT ENCLOSURES: 1 HR.  
 - AT EXIT PASSAGEWAYS: 1 HR.  
 - AT HORIZONTAL EXIT: 2 HRS.  
 - FIRE AREA SEPARATION: 2 HRS.  
 708 FIRE PARTITIONS: 1 HR.  
 713.4 SHAFT ENCLOSURES: 1 HR. (LESS THAN 4 STORES)  
 716 OPENING PROTECTIVES: PER TABLE 716.1(2)  
 - AT FIRE WALLS: 1 1/2 HR.  
 - AT OTHER 2 HR. RATED WALLS: 1 1/2 HR.  
 - AT 1 HR FIRE BARRIERS: 1 HR.  
 - AT EXIT ENCLOSURES: 1 HR.  
 - AT CORRIDOR WALLS: 1 1/2 HR. (WHERE WALLS ARE RATED)

**BUILDING CODE (IBC) ANALYSIS**

**IBC CHAPTER CHAPTER HEADING**

8 INTERIOR FINISHES  
 INTERIOR WALL AND CEILING FINISH MATERIALS SHALL BE CLASSIFIED IN ACCORDANCE WITH ASTM E 84 OR UL 723. INTERIOR FINISH MATERIALS SHALL BE GROUPED IN THE FOLLOWING CLASSES IN ACCORDANCE WITH THEIR FLAME SPREAD AND SMOKE DEVELOPED INDEXES.  
 CLASS A FLAME SPREAD INDEX: 0-25; SMOKE DEVELOPED INDEX: 0-450  
 CLASS B FLAME SPREAD INDEX: 26-75; SMOKE DEVELOPED INDEX: 0-450  
 CLASS C FLAME SPREAD INDEX: 76-300; SMOKE DEVELOPED INDEX: 0-450

TABLE 803.13 INTERIOR WALL AND CEILING FINISH REQUIREMENTS BY OCCUPANCY

GROUP B - SPRINKLERED  
 EXIT ENCLOSURES AND PASSAGEWAYS: B  
 CORRIDORS: C  
 ROOMS AND ENCLOSED SPACES: C

**9 FIRE PROTECTION SYSTEMS**

903.1 AUTOMATIC SPRINKLER SYSTEMS SHALL COMPLY WITH THE SECTION  
 903.5 PORTABLE FIRE EXTINGUISHERS REQUIRED IN GROUP B OCCUPANCY  
 906.1 PORTABLE FIRE EXTINGUISHERS SHALL BE INSTALLED IN ALL OF THE FOLLOWING LOCATIONS:  
 1. IN GROUP B OCCUPANCIES  
 3. IN AREAS WHERE FLAMMABLE OR COMBUSTIBLE LIQUIDS ARE STORED, USED, OR DISPENSED  
 6. SPECIAL HAZARD AREAS, INCLUDING LABORATORIES

TABLE 906.3.1  
 CLASS 2-A FIRE EXTINGUISHERS REQUIRED PER 11,250 SF MAX. AND WITHIN A 75' MAX. TRAVEL DISTANCE

907.2.2 A MANUAL FIRE ALARM SYSTEM SHALL BE INSTALLED IN GROUP B OCCUPANCIES WHERE ONE OF THE FOLLOWING CONDITIONS EXIST: 1. THE COMBINED GROUP B OCCUPANT LOAD OF ALL FLOORS IS 300 OR MORE

**10 MEANS OF EGRESS**

1004.5 MAXIMUM FLOOR AREA ALLOWANCES PER OCCUPANT - TABLE 1004.5  
 (NOTE: NO CHANGE TO OCCUPANCY, AREAS, OR OCCUPANT LOAD)

**BUILDING CODE (IBC) ANALYSIS**

**IBC CHAPTER CHAPTER HEADING**

10 MEANS OF EGRESS (CONTINUED)

**FIRST FLOOR RENOVATED SPACES**

EXISTING TO REMAIN BUSINESS GROUP B SPACES  
 #3308 INORGANIC CHEMISTRY LAB: 1,218 SF @ 50 SF / OCCUPANT = 25 OCCUPANTS  
 #3400 INORGANIC CHEMISTRY LAB: 1,228 SF @ 50 SF / OCCUPANT = 25 OCCUPANTS  
 #3401 ORGANIC CHEMISTRY LAB: 1,202 SF @ 50 SF / OCCUPANT = 24 OCCUPANTS  
 #3402 ORGANIC CHEMISTRY STORAGE: 521 SF @ 300 SF / OCCUPANT = 2 OCCUPANTS  
 #3403 INSTRUMENT ROOM: 561 SF @ 50 SF / OCCUPANT = 12 OCCUPANTS  
 #3404 INORGANIC CHEMISTRY LAB STORAGE: 668 SF @ 300 SF / OCCUPANT = 3 OCCUPANTS

TOTAL FIRST FLOOR RENOVATED SPACES OCCUPANT LOAD: 93 OCCUPANTS

1005.3 MINIMUM REQUIRED EGRESS WIDTH:  
 STAIRWAYS: 0.3' PER OCCUPANT  
 DOORS, RAMPS, AISLES: 0.2' PER OCCUPANT

1006 NUMBER OF EXITS AND EXIT ACCESS DOORWAYS  
 NOTE: NO CHANGES TO TYPE, NUMBER, WIDTH, OR CAPACITY OF EXISTING EXITS

1008.2.1 THE MEANS OF EGRESS ILLUMINATION LEVEL SHALL NOT BE LESS THAN 1 FOOT-CANDLE (1 LUX) AT THE WALKING SURFACE.

1009.1 ACCESSIBLE SPACES SHALL BE SERVED BY NOT LESS THAN TWO ACCESSIBLE MEANS OF EGRESS. PER EXCEPTION 1, ACCESSIBLE MEANS OF EGRESS ARE NOT REQUIRED IN EXISTING BUILDINGS.

1017.2 EXIT ACCESS TRAVEL DISTANCE PER TABLE 1017.2 FOR TYPE 'B' OCCUPANCIES: 300' WITH SPRINKLER SYSTEM


1020.1 CORRIDOR FIRE RESISTANCE RATING PER TABLE 1020.1 FOR TYPE 'B' OCCUPANCY WITH AN OCCUPANT LOAD OF GREATER THAN 30: 1 HOUR WITHOUT SPRINKLER SYSTEM, 0 HOURS WITH SPRINKLER SYSTEM

**11 ACCESSIBILITY**

1102.1 DESIGN - BUILDINGS AND FACILITIES SHALL BE DESIGNED AND CONSTRUCTED TO BE ACCESSIBLE IN ACCORDANCE WITH THIS CODE AND IBC A117.1

**17 STRUCTURAL TESTS AND INSPECTIONS**

NONE



**1 OVERALL CODE SUMMARY PLAN**  
 SCALE: 1/16" = 1'-0"

BUILDING AREAS AND ALTERATION LEVELS		
LEVEL	AREA	% OF TOTAL AREA
FIRST FLOOR	81,712 GSF	100%
TOTAL BUILDING AREA	81,712 GSF	100%
REPAIRS	0 SF	0%
ALTERATIONS - LEVEL 1	4,293 SF	5%
ALTERATIONS - LEVEL 2	1,216 SF	1%
WORK AREA*	1,216 SF	1%

\*DEFINED AS ALL RECONFIGURED SPACES WITHIN BUILDING - LEVEL 2 ALTERATIONS AREA USED AS EQUIVALENT.

**FIRE/EGRESS PLAN LEGEND**

- 1 HR FIRE BARRIER - EXISTING
- TRAVEL DISTANCE
- EXIT TRAVEL DIST XX'-X"
- 30' EGRESS 180 PERSONS
- EXIT DOOR CAPACITY
- ANTICIPATED FURNITURE AND EQUIPMENT (NIC)
- FE ● NEW FIRE EXTINGUISHER
- ACCESSIBLE ROUTE  
ACCESSIBLE ROUTE FROM AN ACCESSIBLE BUILDING ENTRANCE TO AREAS OF PRIMARY FUNCTION, ACCESSIBLE TOILET FACILITIES AND ACCESSIBLE DRINKING FOUNTAINS.

**CODE - BUILDING PLAN LEGEND**

**IEBC CLASSIFICATION OF WORK**


- BUILDING AREA EXTENTS OF BUILDING, NO WORK UNLESS INDICATED BY CATEGORIES BELOW
- ALTERATIONS - LEVEL 1 (CHAPTER 7) REMOVAL AND REPLACEMENT OF EXISTING EQUIPMENT WITH NEW EQUIPMENT TO SERVE THE SAME PURPOSE.
- ALTERATIONS - LEVEL 2 (CHAPTER 8) RECONFIGURATION OF SPACE OR RECONFIGURATION / EXTENSION OF ANY SYSTEM OR INSTALLATION OF ANY ADDITIONAL EQUIPMENT.

Autodesk\_Docs\1104-21-01 Westmoreland CCC - Chem Lab Renovation\21-1104-01\_WCCC Chem Lab Renovation CENTRAL R23.rvt 1/21/2025 2:56:16 PM




A	ANGLE	D	DETAIL	H	HOSE BIBB	O	ON CENTER	SIM	SIMILAR
<	AT	DET	DETAIL	HB	HANDICAPPED	OC	OUTSIDE DIAMETER	SLD	SOLID
AC	AIR CONDITIONING	DF	DRINKING FOUNTAIN	HC	HANGING/PAIRED	OD	OUTSIDE DIAMETER	SPEC	SPECIFY SPECIFIED OR SPECIFICATIONS
AB	ANCHOR BOLT	DI	DIAMETER	HW	HOLLOW-CORE WOOD	OFF	OFFICE	SPKLR	SPRINKLER
ACM	ASBESTOS CONTAINING MATERIALS	DMF	DIFFUSER	HD	HEAD	OPNG	OPENING	SQ	SQUARE
ACOUS	ACOUSTIC	DN	DIMENSION	HDW	HARDWARE	OPP	OPPOSITE	SS	STAINLESS STEEL
ACT	ACOUSTIC CEILING TILE	DR	DIRECTOR	HM	HOLLOW METAL	OZ	OUNCE	SSM	SOLID SURFACE MATERIAL
AD	AREA DRAIN	DN	DOWN	HRZ	HORIZONTAL	PT	PARTITION	ST	STREET
ADJ	ADJUSTABLE	DR	DOOR	HP	HIGH POINT	PC	PERSONAL COMPUTER	STD	STANDARD
AED	AUTOMATED EXTERNAL DEFIBRILLATOR	DWG	DRAWING	HR	HR/HOUR OR HANDRAIL	PED	PEDESTAL	STL	STEEL
AFF	ABOVE FINISHED FLOOR	E	EAST	HT	HT HEIGHT	PERF	PERFORATED	STOR	STORAGE
ALT	ALTERNATE	EA	EACH	HTR	HTR HEATER	FLB	FLUORESCENT LIGHTING	STRUC	STRUCTURAL
ALUM	ALUMINUM	EB	EDGE BANDING	HVAC	HVAC HEATING/VENTILATION/AIR CONDITIONING	FL	FLUTE	SUPPT	SUPPORT(ING)
APPRO	APPROXIMATE(LY)	EJ	EXPANSION JOINT	ICRA	INFECTION CONTROL RISK ASSESSMENT	PLAM	PLASTIC LAMINATE	SURF	SURFACE
ARCH	ARCHITECT OR ARCHITECTURAL	ENCL	ENCLOSURE	EFIS	EXTERIOR INSULATION FINISH SYSTEM	PLAS	PLASTER	SUSP	SUSPEND, SUSPENDED, OR SUSPENSION
ASPH	ASPHALT	EL SHT	ELASTIC SHEET	EJ	EXPANSION JOINT	PLAST	PLASTIC	SY	SQUARE YARD
ASST	ASSISTANT	ELEV	ELEVATOR	EL SHT	ELASTIC SHEET	IN	INCH OR INCHES	SYN	SYNTHETIC
AUTO	AUTOMATIC	ELEC	ELECTRICAL	EXT	EXTERNAL	INCL	INCLUDE, INCLUDED, OR INCLUDING	SYS	SYSTEM
AVG	AVERAGE	ELEV	ELEVATION	EXT	EXTERNAL	INSL	INSULATION	T	TERRAZZO
B	BOTTOM OF	EMER	EMERGENCY	F	FABRIC	INT	INTERIOR	T*	TEE (BAR OR W)
BC	BOTTOM OF CURB	ENCL	ENCLOSURE	FF	FACE TO FACE	J	JOINT	T†	TREAD
BC	BASE CABINET	ENGR	ENGINEER	FAX	FACSIMILE	JAN	JANITOR	TI	TOP OF
BD	BOARD	ENT	ENTRANCE	FBN	FOUNDATION	JMB	JAMB	TIC	TOP OF CURB
BET	BETWEEN	EP	ELECTRICAL PANEL	FE	FIRE EXTINGUISHER	JST	JOIST	TB	TACKBOARD
BEV	BEVELED	EQ	EQUAL	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	JT	JOINT	TC	TERRA COTTA
BIT	BITUMINOUS	EQUIP	EQUIPMENT	FE	FIRE EXTINGUISHER	K	KITCHEN	TEL	TELEPHONE
BLDG	BUILDING	EW	ELECTRIC WATER COOLER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TEMP	TEMPERED OR TEMPERATURE
BLK	BLOCK	EXC	EXCAVATE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TERM	TERMINATE / TERMINAL
BLKG	BLOCKING	EXCL	EXCLUDE(ING)	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TERR	TERRAZZO
BM	BENCH MARK	EXIST	EXISTING	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	THRESH	THRESHOLD
BMK	BENCH MARK	EXP BOLT	EXPANSION BOLT	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TLT	TOILET
BOT	BOTTOM	EXT	EXTERNAL	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TRTD	TREATED
BR	BRICK	F	FABRIC	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TV	TELEVISION
BRG	BEARING	FF	FACE TO FACE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	TYP	TYPICAL
BRKT	BROCKET	FAX	FACSIMILE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	QUAL	QUALITY
BSMT	BASEMENT	FBN	FOUNDATION	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	R	RISER OR ROODS
BUR	BUILT-UP ROOF	FE	FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	LH	LONG LEG HORIZONTAL
C	CHANNEL	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	LV	LONG LEG VERTICAL
CAB	CABINET	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	LP	LOW POINT
CB	CATCH BASIN	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	L	LIGHT
CC	CENTER TO CENTER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	LTL	LINEAL
CEM PL	CEMENT PLASTER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	LTV	LOW POINT
CF	COMPOSITION FLOORING, OR CURB FOOT	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	LWOD	LESS WIDTH OF DOOR
CG	CORNER GUARD	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	M	MASONRY
CJ	CONTROL JOINT	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MAX	MAXIMUM
CL	CENTER LINE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MB	MEMBRANE
CLG	CEILING	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MCL	MARBLE
CLG HT	CEILING HEIGHT	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MCT	MOSAIC CERAMIC TILE
CLO	CLOSET	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MDF	MEDIUM DENSITY FIBREBOARD
CLR	CLEAR	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MECH	MECHANICAL
CLRM	CLASSROOM	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MEMB	MEMBRANE
CMU	CONCRETE MASONRY UNIT	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MEZ	MEZZANINE
CO	CLEAN OUT	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MF	MICROFICHE
COL	COLUMN	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MFR	MANUFACTURE OR MANUFACTURE
CONC	CONCRETE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	MH	MANHOLE
CONN	CONNECTION	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	RTS	RUBBER TRANSITION STRIP
CONST	CONSTRUCTION	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	RWC	RAIN WATER CONDUCTOR
CONT	CONTINUOUS	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	S	SOUTH
CONTR	CONTRACTOR	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SAN	SANITARY
COORD	COORDINATE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SC	SPECIAL COATING
CORR	CORRIDOR	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SCHD	SCHEDULE
CP	COPIER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SCHD	SCHEDULE
CRSE	COURSE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SCVC	SOLID-CORE VINYL CLAD
CS	CONCRETE WISEALER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SCWD	SOLID-CORE WOOD
CT	CERAMIC TILE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SEC	SECTION
CTB	CERAMIC TILE BASE	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SERV	SERVICE
CTR	COUNTER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SF	SQUARE FOOT
CY	CUBIC YARD	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	FEC	FIRE EXTINGUISHER CABINET W/ FIRE EXTINGUISHER	KIT	KITCHEN	SFC	STORE FIXTURE CONTRACTOR

### ARCH - GRAPHIC SYMBOLS LEGEND





### ARCH - GRAPHIC CONVENTIONS LEGEND



#### SECTIONS/ SECTIONAL DETAILS



#### PLANS/ PLAN DETAIL GRAPHICS




### ACCESSIBLE HEIGHTS AND REACH RANGES OF OPERABLE ELEMENTS




### ARCH - PLAN COMPONENTS LEGEND


#### WALL DESIGNATIONS




#### FIRE RATING DESIGNATIONS



#### DOOR DESIGNATIONS



CONTRACTOR IS RESPONSIBLE FOR CONSTRUCTING ALL FIRE PARTITIONS TO MEET IBC 2016 REQUIREMENTS. ALL FIRE PARTITIONS SHALL BE CONSTRUCTED TO FLOOR OR ROOF DECK ABOVE AND SEALED AIR-TIGHT WITH DEFLECTION HEADS AND FIRE SAFING. ALL FIRE PARTITIONS SHALL BE PER ASSEMBLIES NOTED ON WALL TYPES LEGEND, AND EXTEND BEYOND BUILDING ENVELOPE AND BE SEPARATE FROM STRUCTURE AS PER IBC 2016. SEE PLANS FOR LOCATIONS.



**DEMOLITION NOTES**

**EXISTING ROOM NUMBER KEY**

- \*EA-125\* - "E" Denotes existing rooms
- \*A\* Denotes area
- \*125\* Denotes room numbers assigned for field survey

1. THE DEMOLITION PLANS ARE SCHEMATIC AND SHALL SERVE AS A GENERAL GUIDE AND ARE NOT INTENDED TO BE TOTALLY INCLUSIVE. CONTRACTOR IS RESPONSIBLE TO FIELD VERIFY ALL EXISTING CONDITIONS.
2. COORDINATE DEMOLITION ACTIVITIES WITH ALL OTHER CONSTRUCTION IDENTIFIED ON CONSTRUCTION DOCUMENTS.
3. ITEMS SHOWN DASHED ON THE DEMOLITION PLANS SHALL BE REMOVED. TYPICAL UNO KEYNOTES / ARROWS POINT TO A REPRESENTATIVE AMOUNT OF THE DEMOLITION WORK BUT ARE NOT INTENDED TO BE ALL INCLUSIVE.
4. THE FOLLOWING APPLIES TO MASONRY WALLS IDENTIFIED TO BE REMOVED:

IF WALL RESTS ON FLOOR SLAB, SCRAPE FLOOR CLEAN TO RECEIVE NEW FINISH FLOORING. IF WALL EXTENDS BELOW FLOOR SLAB, REMOVE WALL TO 8" BELOW FLOOR SURFACE AND PATCH FLOOR TO MATCH ADJACENT SURFACES UNO

NOTE: FLOOR SLAB ELEVATIONS MAY VARY ON EACH SIDE OF WALL. GC SHALL PATCH / FILL FLOOR SURFACES TO OBTAIN A MAXIMUM 1/8" PER FOOT SLOPE BETWEEN FLOOR SURFACES

5. LINTELS SHALL BE INSTALLED IN NEW OPENINGS IN EXISTING MASONRY WALLS. SEE STRUCTURAL DRAWINGS FOR SIZES.
6. REFER TO SPEC SECTION DIVISION 01 "SELECTIVE DEMOLITION" FOR SPECIFIC REQUIREMENTS REGARDING DEMOLITION SHOWN ON THIS DRAWING.
7. REFER TO SPEC SECTION DIVISION 01 "EXECUTION" FOR SPECIFIC REQUIREMENTS REGARDING CUTTING AND PATCHING SHOWN ON THIS DRAWING.
8. ALL MONITORS, ARTWORK, CLOCKS AND SIGNAGE IN THE WAY OF NEW WORK TO BE SALVAGED AND TURNED OVER TO THE OWNER.
9. GENERAL CONTRACTOR SHALL PATCH/REPAIR EXISTING SURFACES DAMAGED BY REMOVAL OF EXISTING EQUIPMENT, EXISTING CABINETS, EXISTING WALLS, EXISTING ACCESSORIES AND/OR EXISTING SHELVING. CONTRACTOR TO PROVIDE SMOOTH/FLUSH SURFACES IN PREPARATIONS OF NEW FINISH MATERIALS.
10. IF ANY HAZARDOUS MATERIALS OR FINISHES SUSPECT OF HAZARDOUS MATERIAL ARE ENCOUNTERED, NOTIFY THE ARCHITECT IMMEDIATELY AND CEASE WORK IN THE SUSPECTED AREA.
11. ALL FIRE PROTECTION SYSTEM COMPONENTS ARE TO REMAIN AND PROTECTED DURING CONSTRUCTION.

**NUMBERED DEMOLITION NOTES**

NOTE	#
NOTE: NOT ALL NOTES APPEAR ON ALL SHEETS	
1 - FINISHES	
1.1A	REMOVE VINYL COMPOSITION FLOOR TILE & MASTIC. PREP AND PREPARE FOR NEW FINISH
1.1B	EXISTING PAINT ON CONC. SLAB. CLEAN AND PREP PER MANUFACTURER'S WRITTEN INSTRUCTIONS FOR VAPOR CONTROL FOR FLOORING PRODUCT.
1.2A	REMOVE RUBBER BASE & MASTIC. PREP AND PREPARE FOR NEW FINISH
1.3	REMOVE EXISTING ACT CEILING AND FRAMING TO COORDINATE WITH NEW WORK. PREP TO PATCH CEILING SYSTEM AT NEW WORK.
1.3A	EXISTING ACT TO REMAIN. PATCH AND REPAIR CEILING SYSTEM AT NEW WORK.
2 - INTERIOR CONSTRUCTION	
2.1A	REMOVE EXISTING CHALKBOARD
2.1B	REMOVE SLIDING MARKERBOARD DOOR AND ASSOCIATED TRACK
2.2A	REMOVE DOOR FRAME TO REMAIN - SALVAGE DOOR, HARDWARE AND TURN OVER TO OWNER
2.2B	REMOVE DOOR AND FRAME - SALVAGE DOORFRAME, HARDWARE AND TURN OVER TO OWNER
4 - SPECIALTIES & EQUIPMENT	
4.1A	REMOVE PLASTIC LAMINATE/ WOOD/ METAL CASEWORK, COUNTERTOPS, BLOCKING & ASSOCIATED SUPPORTS
4.1B	CAREFULLY REMOVE RESTEK PIPE CHASE AS TO NOT DAMAGE EXISTING CEILING
4.1C	REMOVE FUME HOOD, METAL CASEWORK BELOW, COUNTERTOP, BLOCKING & ASSOCIATED SUPPORTS. DISCONNECT PLUMBING AND CAP FOR NEW HOOD AND SINK. COORDINATE MEP CAP/DISCONNECT WITH MEP CONTRACTORS
4.1D	REMOVE WOOD/METAL SHELVING AND ASSOCIATED HARDWARE
4.1E	REMOVE EXISTING CORROSIVE AND FLAMMABLE STORAGE AND ASSOCIATED VENT PIPING
4.1F	REMOVE EXISTING MISC WALL MOUNTED SHELVING AND TACKBOARDS
7 - MEP COMPONENTS (COORD W/ MEP SERIES DRAWINGS)	
7.1	REMOVE PLUMBING FIXTURES
7.2	REMOVE EXISTING STEAM BOILER, CONCRETE PAD TO REMAIN
7.3	REMOVE EXISTING SMOKE EXHAUST VENT UNIT
7.4	REMOVE EXISTING POWER POLE
7.5	SALVAGE EXISTING ICE MAKER FOR RELOCATION


1 FIRST FLOOR - DEMO PLAN  
AD101 SCALE: 1/4" = 1'-0"



REVISIONS

**CHEM LAB RENOVATIONS | SCIENCE INNOVATION CENTER**  
 161 COMMUNITY COLLEGE DRIVE YOUNGWOOD, PA, 15697  
 WESTMORELAND COUNTY COMMUNITY COLLEGE 145 PAVILLION LANE  
 YOUNGWOOD, PA, 15697  
**FIRST FLOOR - DEMO PLAN**

Proj No. 21-U04-01  
 Issue Date 01/20/2025  
**AD101**  
 © COPYRIGHT 2024



1  
A101 FIRST FLOOR - NEW WORK PLAN  
SCALE: 1/4" = 1'-0"

FUME HOOD COMPONENTS BY TYPE

ITEM NO.	SERVICE					CUP SINK	WORKSURFACE HEIGHT	OVERALL SIZE	OPERATION	CEILING ENCLOSURE	FAN / BLOWER SWITCH	
	AIR	VAC	CW	GAS	STEAM							
H1	NONE	R	L	L	NONE	L/R	MIDDLE REAR - SEE A902	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H2	NONE	L	L	L	NONE	L/R	MIDDLE REAR - SEE A902	39" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H3	L/R	L/R	NONE	L/R	NONE	L/R	EACH SIDE	ADA - 32" TO UNDERSIDE OF HOOD	70" W W/PASS THROUGH, 30" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H4	L	L	L	L	R	L/R	MIDDLE REAR - SEE A902	39" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H5	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A902	39" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H6	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A902	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES

GENERAL PROJECT NOTES

- REFER TO A102 THROUGH A104 FOR ENLARGED PLANS AND CASEWORK ELEVATIONS.
- REFER TO A601 FOR FINISH INFORMATION.
- REFER TO A900 SERIES FOR LAB BENCH DETAILS FOR LAB EQUIPMENT AND FIXTURE TYPES, AND FUME HOOD DETAILS.
- LAB CASEWORK AND FUME HOODS ARE TO BE SOLE SOURCED FROM ONE MANUFACTURER'S PRODUCT OFFERING. DRAWINGS HEREIN PROVIDE GENERAL OVERALL REQUIREMENTS. REFER TO PRODUCT SPECIFICATIONS SECTIONS 11 6100 FUME HOODS AND 12 3535 19 WOOD LABORATORY CASEWORK FOR MORE DETAILED BASIS OF DESIGN PRODUCT INFORMATION.
- EXISTING ACUSTICAL PANEL CEILING IS TO REMAIN. PATCH CEILINGS AS NEEDED IN AREAS OF NEW WORK. SEE A801 / MATERIALS LIST FOR CEILING PANEL AND GRID TYPE.
- SEE LAB BENCH DETAILS FOR LAB EQUIPMENT AND LAB FIXTURE TYPES AND LOCATIONS AT LAB BENCHES.
- SEE LABORATORY FUME HOOD SCHEDULE AND SPECIFICATIONS FOR LAB FIXTURE TYPES AND LOCATIONS AT FUME HOODS.
- EXISTING FLOOR DRAINS TO REMAIN. SLOPE NEW FLOOR AS REQD TO BE COMPLAINT WITH IC A117.1.
- TYPICAL WALL TYPE INDICATORS DISPLAYED ON THE PLANS INDICATE THAT THE PARTITION TYPE IS CONTINUOUS TO A CORNER OR TO AN INTERSECTING PARTITION, UNO.
- WHERE DIFFERENT FLOOR MATERIAL MEET, THEY SHALL MEET UNDER THE CENTERLINE OF THE DOOR, UNLESS OTHERWISE NOTED.
- ALL INTERIOR DIMENSION LINES ARE TO THE FINISH FACE, UNO.
- ALL INTERIOR GPBD FINISH TO BE LEVEL (4), UNO.
- ALL EXISTING GPBD IDENTIFIED FOR NEW FINISH TO BE REPAIRED AND FINISHED THE SAME AS NEW GPBD, SEE SPECIFICATION SECTION 09 91 00.
- ALL EXISTING MASONRY IDENTIFIED FOR NEW FINISH TO BE REPAIRED, SEE SPECIFICATION SECTION 09 91 00.
- EXISTING FIRE PROTECTION SYSTEM COMPONENTS ARE TO REMAIN AND PROTECTED DURING CONSTRUCTION.

CONSTRUCTION NOTES










NUM	DESCRIPTION
1.1	ALIGN FINISH FACES
2.1	PROVIDE AND INSTALL BLOCKING FOR OWNER PROVIDED MONITOR AND MOUNT. COORDINATE LOCATION WITH ARCHITECT

REVISIONS

CHEM LAB RENOVATIONS | SCIENCE INNOVATION CENTER

161 COMMUNITY COLLEGE DRIVE YOUNGWOOD, PA, 15697  
WESTMORELAND COUNTY COMMUNITY COLLEGE 145 PAVILLION LANE  
YOUNGWOOD, PA, 15697

FIRST FLOOR - NEW WORK PLAN



**GENERAL PROJECT NOTES**

- REFER TO A102 THROUGH A104 FOR ENLARGED PLANS AND CASEWORK ELEVATIONS.
- REFER TO A601 FOR FINISH INFORMATION.
- REFER TO A900 SERIES FOR LAB BENCH DETAILS FOR LAB EQUIPMENT AND FIXTURE TYPES, AND FUME HOOD DETAILS.
- LAB CASEWORK AND FUME HOODS ARE TO BE SOLE SOURCED FROM ONE MANUFACTURER'S PRODUCT OFFERING. DRAWINGS HEREIN PROVIDE GENERAL OVERALL REQUIREMENTS. REFER TO PRODUCT SPECIFICATIONS SECTIONS 116100 FUME HOODS AND 1235319 WOOD LABORATORY CASEWORK FOR MORE DETAILED BASIS OF DESIGN PRODUCT INFORMATION.
- EXISTING ACUSTICAL PANEL CEILING IS TO REMAIN. PATCH CEILINGS AS NEEDED IN AREAS OF NEW WORK. SEE A601 MATERIALS LIST FOR CEILING PANEL AND GRID TYPE.
- SEE LAB BENCH DETAILS FOR LAB EQUIPMENT AND LAB FIXTURE TYPES AND LOCATIONS AT LAB BENCHES.
- SEE LABORATORY FUME HOOD SCHEDULE AND SPECIFICATIONS FOR LAB FIXTURE TYPES AND LOCATIONS AT FUME HOODS.
- EXISTING FLOOR DRAINS TO REMAIN. SLOPE NEW FLOOR AS REQ'D TO BE COMPLIANT WITH IIC A117.1.
- TYPICAL WALL TYPE INDICATORS DISPLAYED ON THE PLANS INDICATE THAT THE PARTITION TYPE IS CONTINUOUS TO A CORNER OR TO AN INTERSECTING PARTITION, UNO.
- WHERE DIFFERENT FLOOR MATERIAL MEET, THEY SHALL MEET UNDER THE CENTERLINE OF THE DOOR, UNLESS OTHERWISE NOTED.
- ALL INTERIOR DIMENSION LINES ARE TO THE FINISH FACE, UNO.
- ALL INTERIOR GPBD FINISH TO BE LEVEL (4), UNO.
- ALL EXISTING GPBD IDENTIFIED FOR NEW FINISH TO BE REPAIRED AND FINISHED THE SAME AS NEW GPBD. SEE SPECIFICATION SECTION 09 91 00.
- ALL EXISTING MASONRY IDENTIFIED FOR NEW FINISH TO BE REPAIRED. SEE SPECIFICATION SECTION 09 91 00.
- EXISTING FIRE PROTECTION SYSTEM COMPONENTS ARE TO REMAIN AND PROTECTED DURING CONSTRUCTION.


**GENERAL INTERIOR / CASEWORK NOTES**

- PROVIDE STANDARD LOCKS AT ALL CABINETS UNLESS NOTED OTHERWISE. KEY ALIKE PER ROOM AND MASTER KEY FOR PROJECT.
- VERIFY EQUIPMENT SIZES, WEIGHTS, AND CLEARANCES AND ADJUST CASEWORK ACCORDINGLY.
- PROVIDE FILLER PANELS FOR ALL CASEWORK AND SCRIBE TO WALL.
- ALL COUNTERTOPS TO BE 1" EPOXY RESIN UNLESS NOTED OTHERWISE. PROVIDE 4" HIGH MATCHING EPOXY RESIN BACKSPLASH AGAINST ALL WALLS AND AS NOTED.
- REFER TO SPECIFICATIONS FOR WOOD CASEWORK SPECIES, FINISH, AND HARDWARE TYPES.
- INSTALL RB-1 RESILIENT BASE ON THE BASE OF ALL CASEWORK.
- PAPER TOWEL DISPENSERS AND SOAP DISPENSERS AT EACH SINK LOCATION TO BE FURNISHED BY THE OWNER AND INSTALLED BY THE CONTRACTOR.
- FOR CASEWORK DEPTHS NOT SHOWN IN ELEVATION, SEE A601.
- GC TO VERIFY EXACT MOUNTING LOCATIONS OF ALL ACCESSORIES IN THE FIELD WITH THE ARCHITECT PRIOR TO INSTALLATION.
- GC SHALL PROVIDE AND INSTALL ADDITIONAL FRAMING AND BLOCKING AS REQUIRED FOR ACCESSORY INSTALLATIONS IN STUD WALL AND GPBD PARTITIONS PER THE ACCESSORY MANUFACTURER'S RECOMMENDATIONS.
- PROVIDE FINISHED END PANELS WHERE EXPOSED TO VIEW.

**CASEWORK SCHEDULE**

TAG	DESCRIPTION
BC-1 (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1C1 (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1F (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1M (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1A (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1AM (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (22'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-2C1 (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2F (22'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2M (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2A (22'D)	DOUBLE DOOR CABINET WITH 2 ADJ. SHELVES
BC-5 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-ADA (22'D)	ADA COMPLIANT SINK APRON - METAL (20'D)
BC-ADAM (M)	ADA COMPLIANT SINK APRON - METAL (20'D)
BC-1 (22'D)	SINGLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND ONE 6"H DRAWER
BC-1A (22'D)	SINGLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND ONE 6"H DRAWER
BC-3 (22'D)	DOUBLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND 2 6"H DRAWERS
BC-3A (22'D)	DOUBLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND 2 6"H DRAWERS
BC-3 (20'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-3 (22'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-3A (20'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-4 (22'D)	BASE CABINET WITH 4 EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-S2 (22'D)	DOUBLE DOOR SINK CABINET WITH A 6" HIGH FIXED PANEL AT THE TOP AND A REMOVABLE BACK
BC-S2C1 (20'D)	DOUBLE DOOR BASE CABINET - CORROSIVE STORAGE - METAL
BC-S2F (20'D)	DOUBLE DOOR BASE CABINET - FLAMMABLE STORAGE - METAL
BC-S2M (20'D)	DOUBLE DOOR BASE CABINET WITH TWO ADJUSTABLE SHELVES - METAL
TC-CO	FULL HEIGHT WARDROBE WITH STORAGE SHELF
TC-O1B	OPEN STORAGE CUBBIES WITH 15 COMPARTMENTS
TO-3 (20'D)	OPEN TALL CABINET WITH 3 ADJ. SHELVES
TO-5 (18'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-6 (22'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-6 (24'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-6 (26'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TS-C1 (18'D)	DOUBLE DOOR TALL CABINET WITH 5 ADJ. SHELVES - METAL
TS-2F (16'D)	DOUBLE DOOR TALL CABINET WITH 5 ADJ. SHELVES - METAL
WC-G1	SINGLE DOOR WALL CABINET WITH 2 ADJ. SHELVES WITH GLAZING
WC-G2	DOUBLE DOOR WALL CABINET WITH 2 ADJ. SHELVES WITH GLAZING
WC-S1	42" WIDE FIXED OPEN SHELF (INCLUDE MOUNTING BRACKETS)

**TYPICAL CASEWORK DESIGNATION NOTES**



**NUMBERED INTERIOR/CASEWORK NOTES**

- NOTE: NOT ALL NOTES APPEAR ON EACH SHEET
- FILLER PANEL - SCRIBE TO ADJACENT WALLS. FINISH TO MATCH CASEWORK
- BACKSPLASH TO MATCH COUNTERTOP, 4" HIGH
- PROVIDE 4" BACKSPLASH TO MATCH COUNTERTOP AT ACCESSIBLE HEIGHT LOCATIONS - ALIGN TOP W/ ADJACENT 4" BACKSPLASH
- WATERFALL EDGE AT TRANSITION TO ACCESSIBLE HEIGHT COUNTER - SEE TYPICAL DETAIL
- KNEE SPACE AT ACCESSIBLE SINK LOCATION TO BE REMOVEABLE - SEE TYPICAL DETAIL
- HANGER ROD AND SHELF
- COAT HOOK - 48" AFF

**FUME HOOD COMPONENTS BY TYPE**

ITEM NO.	AIR	VAC	CW	SERVICE GAS	STEAM	DUPLEX REC	CUP SINK	WORKSURFACE HEIGHT	OVERALL SIZE	OPERATION	CEILING ENCLOSURE	FAN / BLOWER SWITCH
H1	NONE	R	L	L	NONE	L/R	MIDDLE REAR - SEE A902	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H2	NONE	L	L	L	NONE	L/R	MIDDLE REAR - SEE A902	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H3	L/R	L/R	NONE	L/R	NONE	L/R	EACH SIDE	ADA - 32" TO UNDERSIDE OF HOOD	70" W W/PASS THROUGH, 30" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H4	L	L	L	L	R	L/R	MIDDLE REAR - SEE A902	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H5	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A902	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H6	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A902	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES

**EQUIPMENT AND FITTINGS LEGEND**

NOTE:	NOT ALL ITEMS APPEAR ON ALL SHEETS
E - LABORATORY EQUIPMENT	
E01	EXISTING FREESTANDING, SELF-CONTAINED NUGGET ICE MAKER - NIC
E02	UNDERCOUNTER LABORATORY GLASSWARE WASHER - LABCONCO STEAMSCRUBBER MODEL # 401001000 OR APPROVED EQUAL
E03	WALL-MOUNTED LABORATORY PEGBOARD W/ DRIP TROUGH (32" X 30") - SEE A9A902
E04	AUTOMATIC WATER DISTILLER - 8 GALLONS PER DAY W/ 4 GALLON RESERVE TANK - DURASTILL MODEL 330 OR APPROVED EQUAL
E05	STEAM BOILER (BY PLUMBING CONTRACTOR) EXIST CONCRETE PAD TO REMAIN
L - LABORATORY DECK MOUNTED FITTINGS AND SINKS (COORD CONNECTIONS W/ MEP CONTRACTORS)	
L01A	DECK MOUNTED LABORATORY BALL VALVES - 2 WAY 180 DEG OUTLET TURRET W/ 2X AIR SERVICE
L01G	DECK MOUNTED LABORATORY BALL VALVES - 2 WAY 180 DEG OUTLET TURRET W/ 2X GAS SERVICE
L01V	DECK MOUNTED LABORATORY BALL VALVES - 2 WAY 180 DEG OUTLET TURRET W/ 2X VACUUM SERVICE
L02A	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, SINGLE WIDE PEDESTAL W/ GFCI RECEPTACLES. RECEPTACLES TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
L02B	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES. 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
L02C	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES. 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS. PROVIDE BLANK AT SECOND FIXTURE EACH SIDE FOR OWNERS DATA CONNECTION.
L03	DECK MOUNTED COMBINATION WATER AND GAS FITTING. FAUCET W/ 6" SPREAD GOOSENECK AND REMOVABLE AERATOR. TWO WAY TURRET W/ GAS OUTLET EACH SIDE.
L04	DECK MOUNTED EMERGENCY EYE WASH AND DRENCH HOSE
L04A	DECK MOUNTED ACCESSIBLE EMERGENCY EYE WASH
L05	DECK MOUNTED MIXING FAUCET
L05A	DECK MOUNTED MIXING FAUCET W/ ACCESSIBLE BLADE HANDLES
L06	INTEGRAL EPOXY RESIN CUP SINK (6" X 3" X 1")
L07	INTEGRAL EPOXY RESIN SINK (25" X 15" X 10")
L07A	INTEGRAL EPOXY RESIN ACCESSIBLE SINK (25" X 15" X 4.5-11" HIGH/LOW)
S - SAFETY EQUIPMENT	
S01	DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR.
S01A	ACCESSIBLE DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR.
S02	FIRE BLANKET CABINET W/ FIRE BLANKET
S03	TYPE A-B-C FIRE EXTINGUISHER W/ BRACKET MOUNT
S04	GAS CYLINDER WALL BRACKET - 8L X 20 X 4 1/4" (1 CYLINDER CAPACITY)

**GENERAL PROJECT NOTES**

- REFER TO A102 THROUGH A104 FOR ENLARGED PLANS AND CASEWORK ELEVATIONS.
- REFER TO A601 FOR FINISH INFORMATION.
- REFER TO A900 SERIES FOR LAB BENCH DETAILS FOR LAB EQUIPMENT AND FIXTURE TYPES, AND FUME HOOD DETAILS.
- LAB CASEWORK AND FUME HOODS ARE TO BE SOLE SOURCED FROM ONE MANUFACTURER'S PRODUCT OFFERING. DRAWINGS HEREIN PROVIDE GENERAL OVERALL REQUIREMENTS. REFER TO PRODUCT SPECIFICATIONS SECTIONS 11.00 FUME HOODS AND 12.00 WOOD LABORATORY CASEWORK FOR MORE DETAILED BASIS OF DESIGN PRODUCT INFORMATION.
- EXISTING ACoustICAL PANEL CEILING IS TO REMAIN. PATCH CEILING AS NEEDED IN AREAS OF NEW WORK. SEE A601 (MATERIALS LIST) FOR CEILING PANEL AND GRID TYPE.
- SEE LAB BENCH DETAILS FOR LAB EQUIPMENT AND LAB FIXTURE TYPES AND LOCATIONS AT LAB BENCHES.
- SEE LABORATORY FUME HOOD SCHEDULE AND SPECIFICATIONS FOR LAB FIXTURE TYPES AND LOCATIONS AT FUME HOODS.
- EXISTING FLOOR DRAINS TO REMAIN. SLOPE NEW FLOOR AS REQ'D TO BE COMPLIANT WITH IIC A117.1.
- TYPICAL WALL TYPE INDICATORS DISPLAYED ON THE PLANS INDICATE THAT THE PARTITION TYPE IS CONTINUOUS TO A CORNER OR TO AN INTERSECTING PARTITION, UNO.
- WHERE DIFFERENT FLOOR MATERIAL MEET, THEY SHALL MEET UNDER THE CENTERLINE OF THE DOOR, UNLESS OTHERWISE NOTED.
- ALL INTERIOR DIMENSION LINES ARE TO THE FINISH FACE, UNO.
- ALL INTERIOR GPBD FINISH TO BE LEVEL (4), UNO.
- ALL EXISTING GPBD IDENTIFIED FOR NEW FINISH TO BE REPAIRED AND FINISHED THE SAME AS NEW GPBD. SEE SPECIFICATION SECTION 09 91 00.
- ALL EXISTING MASONRY IDENTIFIED FOR NEW FINISH TO BE REPAIRED. SEE SPECIFICATION SECTION 09 91 00.
- EXISTING FIRE PROTECTION SYSTEM COMPONENTS ARE TO REMAIN AND PROTECTED DURING CONSTRUCTION.

**GENERAL INTERIOR / CASEWORK NOTES**

- PROVIDE STANDARD LOCKS AT ALL CABINETS UNLESS NOTED OTHERWISE. KEY ALIKE PER ROOM AND MASTER KEY FOR PROJECT.
- VERIFY EQUIPMENT SIZES, WEIGHTS, AND CLEARANCES AND ADJUST CASEWORK ACCORDINGLY.
- PROVIDE FILLER PANELS FOR ALL CASEWORK AND SCRIBE TO WALL.
- ALL COUNTERTOPS TO BE 1" EPOXY RESIN UNLESS NOTED OTHERWISE. PROVIDE 4" HIGH MATCHING EPOXY RESIN BACKSPLASH AGAINST ALL WALLS AND AS NOTED.
- REFER TO SPECIFICATIONS FOR WOOD CASEWORK SPECIES, FINISH, AND HARDWARE TYPES.
- INSTALL RB-1 RESILIENT BASE ON THE BASE OF ALL CASEWORK.
- PAPER TOWEL DISPENSERS AND SOAP DISPENSERS AT EACH SINK LOCATION TO BE FURNISHED BY THE OWNER AND INSTALLED BY THE CONTRACTOR.
- FOR CASEWORK DEPTHS NOT SHOWN IN ELEVATION, SEE A601.
- GC TO VERIFY EXACT MOUNTING LOCATIONS OF ALL ACCESSORIES IN THE FIELD WITH THE ARCHITECT PRIOR TO INSTALLATION.
- GC SHALL PROVIDE AND INSTALL ADDITIONAL FRAMING AND BLOCKING AS REQUIRED FOR ACCESSORY INSTALLATIONS IN STUD WALL AND GPBD PARTITIONS PER THE ACCESSORY MANUFACTURER'S RECOMMENDATIONS.
- PROVIDE FINISHED END PANELS WHERE EXPOSED TO VIEW.

**TYPICAL CASEWORK DESIGNATION NOTES**

# DESIGNATES CABINET CATEGORY (SEE A601)    xx-xx    # DESIGNATES CABINET TYPE (SEE A601)  
 # DESIGNATES CASEWORK WIDTH (SEE ELEVATIONS)    x    X

(C) = CORROSIVE  
 (F) = FLAMMABLE  
 (M) = METAL  
 \* IF NO DESIGNATION, CABINET TO BE WOOD












**NUMBERED INTERIOR/CASEWORK NOTES**

NOTE: NOT ALL NOTES APPEAR ON EACH SHEET

1	FILLER PANEL - SCRIBE TO ADJACENT WALLS. FINISH TO MATCH CASEWORK
2	BACKSPLASH TO MATCH COUNTERTOP, 4" HIGH
3	PROVIDE 6" BACKSPLASH TO MATCH COUNTERTOP AT ACCESSIBLE HEIGHT LOCATIONS - ALIGN TOP WITH ADJACENT 4" BACKSPLASH
4	WATERFALL EDGE AT TRANSITION TO ACCESSIBLE HEIGHT COUNTER - SEE TYPICAL DETAIL
5	KNEE SPACE AT ACCESSIBLE SINK LOCATION TO BE REMOVEABLE - SEE TYPICAL DETAIL
6	HANGER ROD AND SHELF
7	COAT HOOK - 48" AFF

**CASEWORK SCHEDULE**

TAG	DESCRIPTION
BC-1 (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1 (F) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1 (M) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1A (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1A (M) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (22'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-2 (F) (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (M) (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2A (22'D)	DOUBLE DOOR CABINET WITH 2 ADJ. SHELVES
BC-2 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-ADA (22'D)	ADA COMPLIANT SINK APRON - METAL (20'D)
BC-ADA (M)	ADA COMPLIANT SINK APRON - METAL (20'D)
BC-C1 (22'D)	SINGLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND ONE 6"H DRAWER
BC-C1A (22'D)	SINGLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND ONE 6"H DRAWER
BC-C3 (22'D)	DOUBLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND 2 6" H DRAWERS
BC-C3A (22'D)	DOUBLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND 2 6" H DRAWERS
BC-C3 (20'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-D3 (22'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-D3A (20'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-L (22'D)	BASE CABINET WITH 4 EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-S2 (22'D)	DOUBLE DOOR SINK CABINET WITH A 6" HIGH FIXED PANEL AT THE TOP AND A REMOVEABLE BACK
BC-S2(C) (20'D)	DOUBLE DOOR BASE CABINET - CORROSIVE STORAGE - METAL
BC-S2(F) (20'D)	DOUBLE DOOR BASE CABINET - FLAMMABLE STORAGE - METAL
BC-S2(M) (20'D)	DOUBLE DOOR BASE CABINET WITH TWO ADJUSTABLE SHELVES - METAL
TC-00	FULL HEIGHT WARDROBE WITH STORAGE SHELF
TC-018	OPEN STORAGE CUBBIES WITH 18 COMPARTMENTS
TO-3 (24'D)	OPEN TALL CABINET WITH 3 ADJ. SHELVES
TO-5 (18'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-5 (22'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-5 (24'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-5 (26'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TS-2(C) (18'D)	DOUBLE DOOR TALL CABINET WITH 5 ADJ. SHELVES - METAL
TS-2(F) (18'D)	DOUBLE DOOR TALL CABINET WITH 5 ADJ. SHELVES - METAL
WC-G1	SINGLE DOOR WALL CABINET WITH 2 ADJ. SHELVES WITH GLAZING
WC-G2	DOUBLE DOOR WALL CABINET WITH 2 ADJ. SHELVES WITH GLAZING
WC-S1	42" WIDE FIXED OPEN SHELF (INCLUDE MOUNTING BRACKETS)



**EQUIPMENT AND FITTINGS LEGEND**

NOTE: NOT ALL ITEMS APPEAR ON ALL SHEETS  
 E - LABORATORY EQUIPMENT

E01	EXISTING FREESTANDING, SELF-CONTAINED NUGGET ICE MAKER - NIC
E02	UNDERCOUNTER LABORATORY GLASSWARE WASHER - LABCONCO STEAMSCRUBBER MODEL # 40101000 OR APPROVED EQUAL
E03	WALL MOUNTED LABORATORY PEGBOARD W/ DRIP TROUGH (32" X 30") - SEE A1A902
E04	AUTOMATIC WATER DISTILLER - 8 GALLONS PER DAY W/ 4 GALLON RESERVE TANK - DURASTILL MODEL 301 OR APPROVED EQUAL
E05	STEAM BOILER (BY PLUMBING CONTRACTOR) EXIST CONCRETE PAD TO REMAIN
L1	LABORATORY DECK MOUNTED FITTINGS AND SINKS (COORD CONNECTIONS W/ MEP CONTRACTORS)
LD1A	DECK MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X GAS SERVICE
LD1G	DECK MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X GAS SERVICE
LD1V	DECK MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X VACUUM SERVICE
LD2A	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, SINGLE WIDE PEDESTAL W/ GFCI RECEPTACLES. RECEPTACLES TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
LD2B	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES. 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
LD2C	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES. 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS. PROVIDE BLANK AT SECOND FIXTURE EACH SIDE FOR OWNER'S DATA CONNECTION
LD3	DECK MOUNTED COMBINATION WATER AND GAS FITTING. FAUCET W/ 8" SPREAD GOOSENECK AND REMOVEABLE AERATOR. TWO WAY TURRET W/ GAS OUTLET EACH SIDE.
L04	DECK MOUNTED EMERGENCY EYE WASH AND DRENCH HOSE
LD4A	DECK MOUNTED ACCESSIBLE EMERGENCY EYE WASH
L05	DECK MOUNTED MIXING FAUCET
LD5A	DECK MOUNTED MIXING FAUCET W/ ACCESSIBLE BLADE HANDLES
L06	INTEGRAL EPOXY RESIN CUP SINK (6" X 7.5")
L07	INTEGRAL EPOXY RESIN SINK (25" X 15" X 10")
LD7A	INTEGRAL EPOXY RESIN ACCESSIBLE SINK (25" X 15" X 4.5-11" HIGH-LOW)



S - SAFETY EQUIPMENT

SS1	DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR.
SS1A	ACCESSIBLE DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR.
SS2	FIRE BLANKET CABINET W/ FIRE BLANKET
SS3	TYPE A-B-C FIRE EXTINGUISHER W/ BRACKET MOUNT
SS4	GAS CYLINDER WALL BRACKET - 8L X 2D X 4H (1 CYLINDER CAPACITY)


**FUME HOOD COMPONENTS BY TYPE**

ITEM NO.	AIR VAC	WC	CL	GAS	STEAM	DUPLEX REC.	CUP SINK	WORKSURFACE HEIGHT	OVERALL SIZE	OPERATION	CEILING ENCLOSURE	FAN / BLOWER SWITCH
H1	NONE	R	L	L	NONE	L/R	MIDDLE REAR - SEE A902	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H2	NONE	L	L	L	NONE	L/R	MIDDLE REAR - SEE A902	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H3	L/R	L/R	NONE	L/R	NONE	L/R	EACH SIDE	ADA - 32" TO UNDERSIDE OF HOOD	70" W/ WIPASS THROUGH, 30" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H4	L	L	L	L	R	L/R	MIDDLE REAR - SEE A902	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H5	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A902	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H6	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A902	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES






**1 ENLARGED FLOOR PLAN - RM 3401**  
 SCALE: 1/4" = 1'-0"




**6 ENLARGED FLOOR PLAN - RM 3402**  
 SCALE: 1/4" = 1'-0"

**NUMBERED INTERIOR/CASEWORK NOTES**


NOTE:	NOT ALL NOTES APPEAR ON EACH SHEET.
1	FILLER PANEL - SCRIBE TO ADJACENT WALLS. FINISH TO MATCH CASEWORK
2	BACKSPLASH TO MATCH COUNTERTOP. 4" HIGH
3	PROVIDE 6" BACKSPLASH TO MATCH COUNTERTOP AT ACCESSIBLE HEIGHT LOCATIONS - ALIGN TOP W/ ADJACENT 4" BACKSPLASH
4	WATERFALL EDGE AT TRANSITION TO ACCESSIBLE HEIGHT COUNTER - SEE TYPICAL DETAIL
5	KNEE SPACE AT ACCESSIBLE SINK LOCATION TO BE REMOVABLE - SEE TYPICAL DETAIL
6	HANGER ROD AND SHELF
7	COAT HOOK - 46" AFF




**7 CASEWORK ELEVATION**  
 SCALE: 1/4" = 1'-0"




**8 CASEWORK ELEVATION**  
 SCALE: 1/4" = 1'-0"




**9 CASEWORK ELEVATION**  
 SCALE: 1/4" = 1'-0"



**10 CASEWORK ELEVATION**  
 SCALE: 1/4" = 1'-0"



**11 CASEWORK ELEVATION**  
 SCALE: 1/4" = 1'-0"



**12 CASEWORK ELEVATION**  
 SCALE: 1/4" = 1'-0"

**TYPICAL CASEWORK DESIGNATION NOTES**

# DESIGNATES CABINET CATEGORY (SEE A601)    --X-#X-#    # DESIGNATES CABINET TYPE (SEE A601)  
 # DESIGNATES CASEWORK WIDTH (SEE ELEVATIONS)  
 (C) = CORROSIVE  
 (F) = FLAMMABLE  
 (M) = METAL  
 \* IF NO DESIGNATION, CABINET TO BE WOOD

**FUME HOOD COMPONENTS BY TYPE**

ITEM NO.	AIR	VAC	CW	GAS	STEAM	DUPLEX REC	CUP SINK	WORKSURFACE HEIGHT	OVERALL SIZE	OPERATION	CEILING ENCLOSURE	FAN / BLOWER SWITCH
H1	NONE	R	L	L	NONE	L/R	MIDDLE REAR - SEE A802	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H2	NONE	L	L	L	NONE	L/R	MIDDLE REAR - SEE A802	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H3	L/R	L/R	NONE	L/R	NONE	L/R	EACH SIDE	ADA - 32" TO UNDERSIDE OF HOOD	70" W WIPASS THROUGH, 30" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H4	L	L	L	L	R	L/R	MIDDLE REAR - SEE A802	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H5	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A802	35" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES
H6	L/R	L/R	L/R	L/R	L/R	L/R	MIDDLE REAR - SEE A802	ADA - 32" TO UNDERSIDE OF HOOD	72" W, 24" DEPTH, 28" VERTICAL SASH OPENING	CONSTANT VOLUME CFM 785	TO 6" ABOVE EXISTING CEILING	YES

**GENERAL INTERIOR / CASEWORK NOTES**

- PROVIDE STANDARD LOOK AT ALL CABINETS UNLESS NOTED OTHERWISE. KEY ALIKE PER ROOM AND MASTER KEY FOR PROJECT.
- VERIFY EQUIPMENT SIZES, WEIGHTS, AND CLEARANCES AND ADJUST CASEWORK ACCORDINGLY.
- PROVIDE FILLER PANELS FOR ALL CASEWORK AND SCRIBE TO WALL.
- ALL COUNTERTOPS TO BE 1" EPOXY RESIN UNLESS NOTED OTHERWISE. PROVIDE 4" HIGH MATCHING EPOXY RESIN BACKSPLASH AGAINST ALL WALLS AND AS NOTED.
- REFER TO SPECIFICATIONS FOR WOOD CASEWORK SPECIES, FINISH, AND HARDWARE TYPES.
- INSTALL RB-1 RESILIENT BASE ON THE BASE OF ALL CASEWORK.
- PAPER TOWEL DISPENSERS AND SOAP DISPENSERS AT EACH SINK LOCATION TO BE FURNISHED BY THE OWNER AND INSTALLED BY THE CONTRACTOR.
- FOR CASEWORK DEPTHS NOT SHOWN IN ELEVATION, SEE A601.
- GC TO VERIFY EXACT MOUNTING LOCATIONS OF ALL ACCESSORIES IN THE FIELD WITH THE ARCHITECT PRIOR TO INSTALLATION.
- GC SHALL PROVIDE AND INSTALL ADDITIONAL FRAMING AND BLOCKING AS REQUIRED FOR ACCESSORY INSTALLATIONS IN STUD WALL AND GPBD PARTITIONS PER THE ACCESSORY MANUFACTURER'S RECOMMENDATIONS.
- PROVIDE FINISHED END PANELS WHERE EXPOSED TO VIEW.

**GENERAL PROJECT NOTES**

- REFER TO A102 THROUGH A104 FOR ENLARGED PLANS AND CASEWORK ELEVATIONS.
- REFER TO A601 FOR FINISH INFORMATION.
- REFER TO A800 SERIES FOR LAB BENCH DETAILS FOR LAB EQUIPMENT AND FIXTURE TYPES, AND FUME HOOD DETAILS.
- LAB CASEWORK AND FUME HOODS ARE TO BE SOLE SOURCED FROM ONE MANUFACTURER'S PRODUCT OFFERING. DRAWINGS HEREIN PROVIDE GENERAL OVERALL REQUIREMENTS. REFER TO PRODUCT SPECIFICATIONS SECTIONS 11 6100 FUME HOODS AND 12 3633 19 WOOD LABORATORY CASEWORK FOR MORE DETAILED BASIS OF DESIGN PRODUCT INFORMATION.
- EXISTING ACoustICAL PANEL CEILING IS TO REMAIN. PATCH CEILINGS AS NEEDED IN AREAS OF NEW WORK. SEE A601 MATERIALS LIST FOR CEILING PANEL AND GRID TYPE.
- SEE LAB BENCH DETAILS FOR LAB EQUIPMENT AND LAB FIXTURE TYPES AND LOCATIONS AT LAB BENCHES.
- SEE LABORATORY FUME HOOD SCHEDULE AND SPECIFICATIONS FOR LAB FIXTURE TYPES AND LOCATIONS AT FUME HOODS.
- EXISTING FLOOR DRAINS TO REMAIN. SLOPE NEW FLOOR AS REQ'D TO BE COMPLIANT WITH IIC A117.1.
- TYPICAL WALL TYPE INDICATORS DISPLAYED ON THE PLANS INDICATE THAT THE PARTITION TYPE IS CONTINUOUS TO A CORNER OR TO AN INTERSECTING PARTITION, UNO.
- WHERE DIFFERENT FLOOR MATERIAL MEET, THEY SHALL MEET UNDER THE CENTERLINE OF THE DOOR, UNLESS OTHERWISE NOTED.
- ALL INTERIOR DIMENSION LINES ARE TO THE FINISH FACE, UNO.
- ALL INTERIOR GPBD FINISH TO BE LEVEL (4), UNO.
- ALL EXISTING GPBD IDENTIFIED FOR NEW FINISH TO BE REPAIRED AND FINISHED THE SAME AS NEW GPBD. SEE SPECIFICATION SECTION 09 91 00.
- ALL EXISTING MASONRY IDENTIFIED FOR NEW FINISH TO BE REPAIRED. SEE SPECIFICATION SECTION 09 91 00.
- EXISTING FIRE PROTECTION SYSTEM COMPONENTS ARE TO REMAIN AND PROTECTED DURING CONSTRUCTION.

**CASEWORK SCHEDULE**


TAG	DESCRIPTION
BC-1 (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1(C) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1(F) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1(M) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-1A (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-1A(M) (20'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2 (22'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-2(C) (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2(F) (22'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2(M) (20'D)	DOUBLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES - METAL
BC-2A (22'D)	DOUBLE DOOR CABINET WITH 2 ADJ. SHELVES
BC-3 (22'D)	SINGLE DOOR BASE CABINET WITH 2 ADJUSTABLE SHELVES
BC-ADA (22'D)	ADA COMPLIANT SINK APRON
BC-ADAM (20'D)	ADA COMPLIANT SINK APRON - METAL (20'D)
BC-C1 (22'D)	SINGLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND ONE 6" H DRAWER
BC-C1A (22'D)	SINGLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND ONE 6" H DRAWER
BC-C3 (22'D)	DOUBLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND 2 6" H DRAWERS
BC-C3A (22'D)	DOUBLE DOOR BASE CABINET WITH ONE ADJUSTABLE SHELF AND 2 6" H DRAWERS
BC-D3 (20'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-D3 (22'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-D3A (20'D)	BASE CABINET WITH THREE EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-L (22'D)	BASE CABINET WITH 4 EQUAL DRAWERS - INCLUDE PADLOCK HASPS
BC-S2 (22'D)	DOUBLE DOOR SINK CABINET WITH A 6" HIGH FIXED PANEL AT THE TOP AND A REMOVABLE BACK
BC-S2(C) (20'D)	DOUBLE DOOR BASE CABINET - CORROSIVE STORAGE - METAL
BC-S2(F) (20'D)	DOUBLE DOOR BASE CABINET - FLAMMABLE STORAGE - METAL
BC-S2(M) (20'D)	DOUBLE DOOR BASE CABINET WITH TWO ADJUSTABLE SHELVES - METAL
TC-CO	FULL HEIGHT WARDROBE WITH STORAGE SHELF
TC-O18	OPEN STORAGE CUBBIES WITH 18 COMPARTMENTS
TO-3 (24'D)	OPEN TALL CABINET WITH 3 ADJ. SHELVES
TO-5 (18'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-5 (22'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-5 (24'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TO-5 (26'D)	OPEN TALL CABINET WITH 5 ADJ. SHELVES
TS-2(C) (18'D)	DOUBLE DOOR TALL CABINET WITH 5 ADJ. SHELVES - METAL
TS-2(F) (18'D)	DOUBLE DOOR TALL CABINET WITH 5 ADJ. SHELVES - METAL
WC-G1	SINGLE DOOR WALL CABINET WITH 2 ADJ. SHELVES WITH GLAZING
WC-G2	DOUBLE DOOR WALL CABINET WITH 2 ADJ. SHELVES WITH GLAZING
WC-S1	42" WIDE FIXED OPEN SHELF (INCLUDE MOUNTING BRACKETS)

**EQUIPMENT AND FITTINGS LEGEND**

NOTE: NOT ALL ITEMS APPEAR ON ALL SHEETS  
 E - LABORATORY EQUIPMENT

E01	EXISTING FREESTANDING, SELF-CONTAINED NUGGET ICE MAKER - NIC
E02	UNDERCOUNTER LABORATORY GLASSWARE WASHER - LABCONCO STEAMSCRUBBER MODEL # 401010200 PROVIDED EQUAL
E03	WALL MOUNTED LABORATORY PEGBOARD W/ DRIP TROUGH (32" X 30") - SEE SA8902
E04	AUTOMATIC WATER DISTILLER - 8 GALLONS PER DAY W/ 4 GALLON RESERVE TANK - DURASTILL MODEL 30J OR APPROVED EQUAL
E05	STEAM BOLLER (BY PLUMBING CONTRACTOR) EXIST CONCRETE PAD TO REMAIN
L-1	LABORATORY DECK MOUNTED FITTINGS AND SINKS (COORD CONNECTIONS W/ MEP CONTRACTORS)
L01A	DECK MOUNTED LABORATORY BALL VALVES - 2 WAY 180 DEG. OUTLET TURRET W/ 2X AIR SERVICE
L01G	DECK MOUNTED LABORATORY BALL VALVES - 2 WAY 180 DEG. OUTLET TURRET W/ 2X GAS SERVICE
L01V	DECK MOUNTED LABORATORY BALL VALVES - 2 WAY 180 DEG. OUTLET TURRET W/ 2X VACUUM SERVICE
L02A	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, SINGLE WIDE PEDESTAL W/ GFCI RECEPTACLES, RECEPTACLES TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
L02B	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES, 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
L02C	DECK MOUNTED ELECTRICAL FIXTURE - DOUBLE FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES, 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS. PROVIDE BLANK AT SECOND FIXTURE EACH SIDE FOR OWNER'S DATA CONNECTION
L03	DECK MOUNTED COMBINATION WATER AND GAS FITTING, FAUCET W/ 6" SPREAD GOOSENECK AND REMOVABLE AERATOR, TWO WAY TURRET W/ GAS OUTLET EACH SIDE
L04	DECK MOUNTED EMERGENCY EYE WASH AND DRENCH HOSE
L04A	DECK MOUNTED ACCESSIBLE EMERGENCY EYE WASH
L05	DECK MOUNTED MIXING FAUCET
L05A	DECK MOUNTED MIXING FAUCET W/ ACCESSIBLE BLADE HANDLES
L06	INTEGRAL EPOXY RESIN CUP SINK (6" X 3" X 7")
L07	INTEGRAL EPOXY RESIN SINK (25" X 15" X 10")
L07A	INTEGRAL EPOXY RESIN ACCESSIBLE SINK (25" X 15" X 4.5" HIGH-LOW)
S	SAFETY EQUIPMENT
S01	DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR.
S01A	ACCESSIBLE DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR.
S02	FIRE BLANKET CABINET W/ FIRE BLANKET
S03	TYPE A-B-C FIRE EXTINGUISHER W/ BRACKET MOUNT
S04	GAS CYLINDER WALL BRACKET - 8L X 20 X 4" (1 CYLINDER CAPACITY)





DOOR NUMBER	WIDTH	HEIGHT	THICKNESS	DOOR PANEL			FRAME			RATING	HARDWARE SET	REMARKS
				TYPE	MATERIAL	GLAZING	TYPE	MATERIAL	GLAZING			
3391	3'-0"	7'-0"	1 3/4"	FG	WD	1	1 (EXIST)	EXIST	---	90 MIN	1	NEW TRANSOM PANEL IN EXISTING HOLLOW METAL FRAME. EXISTING DOOR FRAME TO BE PAINTED.
3401	3'-0"	7'-0"	1 3/4"	FG	WD	1	1 (EXIST)	EXIST	---	90 MIN	1	NEW TRANSOM PANEL IN EXISTING HOLLOW METAL FRAME. EXISTING DOOR FRAME TO BE PAINTED.
3401/1	3'-0"	7'-0"	1 3/4"	FG	WD	1	1 (EXIST)	EXIST	---	90 MIN	1	NEW TRANSOM PANEL IN EXISTING HOLLOW METAL FRAME. EXISTING DOOR FRAME TO BE PAINTED.
3401/2	3'-0"	7'-0"	1 3/4"	EXIST	EXIST	EXIST	2 (EXIST)	EXIST	---	EXIST	4	EXISTING DOOR AND FRAME TO BE PAINTED
3402/1	3'-0"	7'-0"	1 3/4"	NL	WD	1	2 (EXIST)	EXIST	---	90 MIN	3	EXISTING DOOR FRAME TO BE PAINTED
3403/1	3'-0"	7'-0"	1 3/4"	NL	WD	1	2 (EXIST)	EXIST	---	90 MIN	3	EXISTING DOOR FRAME TO BE PAINTED
3403/2	3'-0"	7'-0"	1 3/4"	NL	WD	1	2 (EXIST)	EXIST	---	90 MIN	3	EXISTING DOOR FRAME TO BE PAINTED
3403/3	3'-0"	7'-0"	1 3/4"	NL	WD	1	3 (NEW)	HM	---	90 MIN	2	EXISTING DOOR FRAME TO BE PAINTED
3404/1	3'-0"	7'-0"	1 3/4"	NL	WD	1	3 (NEW)	HM	---	90 MIN	3	
3404/2	3'-0"	7'-0"	1 3/4"	NL	WD	1	3 (NEW)	HM	---	90 MIN	3	

**NOTES - GENERAL DOOR NOTES**

- ALL NEW WOOD DOORS TO MATCH EXISTING WITH A CUSTOM STAIN. ARCHITECT TO SELECT A SAMPLE DOOR FOR GC TO MATCH.
- EXISTING DOORS AND FRAMES TO REMAIN TO BE REPAIRED, FILLED, FILED, SANDED, PRIMED, AND PAINTED, PNT-3.
- APPLIED STOPS SHALL BE ON INTERIOR (LOCKED ROOM) SIDE OF HOLLOW METAL FRAME - TYPICAL.
- ALL RATED OPENINGS SHALL HAVE MATCHING RATED FRAMES, AND HAVE UL LISTED DOOR HARDWARE. LABELED TAGS SHALL NOT BE PAINTED.
- GENERAL CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS.
- DOOR HARDWARE SET TYPES LISTED TO INDICATE DOOR OPERATION AND ANY SPECIAL CONDITIONS FOR THE DOOR TYPE. FOR EACH HARDWARE SET TYPE PROVIDE ALL REQUIRED DOOR HARDWARE FOR A FULLY FUNCTIONAL DOOR - INCLUDING LATCH SETS, LEVERS, HINGES, CLOSERS, LOCK AND LATCH STRIKES, DOOR STOPS, GASKETING AND TRIM, ETC.
- DOOR HARDWARE MAKE, MODEL, STYLE, AND FINISHES TO MATCH EXISTING STANDARDS.
- ALL NEW HM DOOR FRAMES TO BE PAINTED, PNT-3.

**ARCH - GLAZING LEGEND**

TYP INTERIOR UNO  
1/4" TEMPERED GLASS - 90 MIN

**MATERIALS LIST**

**ACOUSTICAL CEILING TILE**

ACT-1 = ARMSTRONG  
STYLE CALLA  
SIZE: 2' x 4' w/ 8" GRID  
FOR PATCHING / MATCH EXISTING

**RUBBER BASE**

RB-1 = JOHNSONITE/TARKETT  
TRADITIONAL COVE  
SIZE: 4"  
COLOR: CHARCOAL  
OUTSIDE CORNERS: PREMOLDED

**RUBBER FLOORING**


RF-1 = NORA FLOORING  
NORAPLAN ENVIRONCARE  
COLOR: TOST FUN RUN  
SIZE: 24" X 24"  
THICKNESS: 3MM  
NOTE: APPLY VAPOR CONTROL TO EXISTING CONCRETE SLAB PRIOR TO FLOORING INSTALLATION. SEE SPECIFICATIONS FOR MORE DETAIL.

**PAINT**


PNT-1 = SHERWIN WILLIAMS  
COLOR: HERON PLUME SW 6070  
LOCATION: FIELD

PNT-2 = SHERWIN WILLIAMS  
COLOR: REGATTA SW 6517  
LOCATION: ACCENT

PNT-3 = SHERWIN WILLIAMS  
COLOR: DOVETAIL SW 7018  
LOCATION: HOLLOW METAL DOORS/  
FRAMES



**3 FIRST FLOOR - SIGNAGE PLAN**  
SCALE: 1/8" = 1'-0"



**ARCH - DOOR TYPES**


**ARCH - FRAME TYPES**

**LIST OF DOOR ABBREVIATIONS**


ALUM	ALUMINUM
BD	BARN DOOR
ELEV	ELEVATION(S)
EXIST	EXISTING
F	FLUSH
FAC	FACTORY
FG	FULL GLASS
(FV)	FIELD VERIFY
FR	FIRE RATED
FRSG	FIRE RATED SAFETY GLAZING
GL	GLAZING
HM	HOLLOW METAL
HR	HOUR
INSUL	INSULATED
PR	PAIR
PNT	PAINT
PNL	PANEL
TEMP	TEMPERED
SCWD	SOLID CORE WOOD
SD	SLIDING DOOR
S + V	STAIN AND VARNISH
WFC	WOOD-FRAMED CURTAINWALL SYSTEM

**ROOM FINISH SCHEDULE**


NUM	ROOMS	FLOOR	BASE	WALLS				CEILING	COMMENTS
				NORTH	EAST	SOUTH	WEST		
3308	INORGANIC CHEM LAB	RF-1	RB-1	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	ACT-1/PATCH AS NEEDED	
3400	INORGANIC CHEM LAB	RF-1	RB-1	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	ACT-1/PATCH AS NEEDED	
3401	ORGANIC CHEM LAB	RF-1	RB-1	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	ACT-1/PATCH AS NEEDED	
3402	ORGANIC CHEM STOR	RF-1	RB-1	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	ACT-1/PATCH AS NEEDED	
3403	INSTRUMENT ROOM	RF-1	RB-1	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	ACT-1/PATCH AS NEEDED	
3404	INORGANIC CHEM STOR	RF-1	RB-1	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	PNT-1/PNT-2	ACT-1/PATCH AS NEEDED	



**1 TYPICAL WALL FINISH ELEVATION**  
SCALE: 3/8" = 1'-0"




**2 TYPICAL VISUAL DISPLAY BOARDS**  
SCALE: 1/4" = 1'-0"




**BASE CABINETS (STANDARD HEIGHT)**

SCALE: 1/2" = 1'-0"




**BASE CABINETS (ACCESSIBLE HEIGHT)**

SCALE: 1/2" = 1'-0"



**TALL CABINETS**

SCALE: 1/2" = 1'-0"




**WALL CABINETS**

SCALE: 1/2" = 1'-0"

**GENERAL SIGNAGE NOTES**


- PROVIDE BACKER PLATES WHERE SIGNS ARE MOUNTED ON GLASS.
- COORDINATE IN THE FIELD. ALL SIGNAGE PLACEMENT WITH THE ARCHITECT.
- MOUNTING HEIGHT TO BE 60" ABOVE FLOOR MAX TO BASELINE OF HIGHEST TACTILE CHARACTER. MOUNT ON LATCH SIDE. SIGNS CONTAINING TACTILE CHARACTERS SHALL BE LOCATED SO THAT A CLEAR FLOOR AREA 18" MIN X 18" MIN, CENTERED ON THE TACTILE CHARACTERS. IF MIN CLEAR FLOOR AREA IS NOT AVAILABLE AT LATCH SIDE, LOCATE SIGN ON NEAREST ADJACENT WALL WITH CLEAR FLOOR AREA.
- SIGN LAYOUT, SIZE, AND COLOR TO BE APPROVED BY ARCHITECT.
- FOR FINISH SELECTION SEE COLOR SCHEDULE, TBD BY ARCHITECT.
- SIGNS TO BE FABRICATED AND INSTALLED IN COMPLIANCE WITH ICC A117.1, 2009.
- ALL TEXT AND SYMBOLS TO BE RAISED UNO.
- ALL SIGNAGE TYPE, ROOM NAME, AND ROOM NUMBER TO BE COORDINATED WITH THE ARCHITECT.




**4 SIGNAGE TYPE**  
SCALE: 3" = 1'-0"

**TYPICAL CASEWORK DESIGNATION NOTES**


# DESIGNATES CABINET CATEGORY (SEE A601) → XX-XX → # DESIGNATES CABINET TYPE (SEE A601)  
# DESIGNATES CASEWORK WIDTH (SEE ELEVATIONS)  
(C) = CORROSIVE  
(F) = FLAMMABLE  
(M) = METAL  
\* IF NO DESIGNATION, CABINET TO BE WOOD




1 PLAN - LAB BENCH TYPE A  
SCALE: 3/4" = 1'-0"




3 PLAN - LAB BENCH TYPE B (ACCESSIBLE)  
SCALE: 3/4" = 1'-0"




5 PLAN - LAB BENCH TYPE C  
SCALE: 3/4" = 1'-0"




7 PLAN - LAB BENCH TYPE D  
SCALE: 3/4" = 1'-0"




9 PLAN - LAB BENCH TYPE E (ACCESSIBLE)  
SCALE: 3/4" = 1'-0"




4 ELEVATION - LAB BENCH TYPE A  
SCALE: 3/4" = 1'-0"




2 ELEVATION - LAB BENCH TYPE B (ACCESSIBLE)  
SCALE: 3/4" = 1'-0"



6 ELEVATION - LAB BENCH TYPE C  
SCALE: 3/4" = 1'-0"



8 ELEVATION - LAB BENCH TYPE D  
SCALE: 3/4" = 1'-0"



10 ELEVATION - LAB BENCH TYPE E (ACCESSIBLE)  
SCALE: 3/4" = 1'-0"

**EQUIPMENT AND FITTINGS LEGEND**

NOTE: NOT ALL ITEMS APPEAR ON ALL SHEETS

E - LABORATORY EQUIPMENT

E01 EXISTING FREESTANDING, SELF-CONTAINED MUGGET ICE MAKER - NIC

E02 UNDERCOUNTER LABORATORY GLASSWARE WASHER - LABCONCO STEAMSCRUBBER MODEL # 4001000 OR APPROVED EQUAL

E03 WALL-MOUNTED LABORATORY PEGBOARD W/ DRIP TROUGH (32"W X 30"H) - SEE SA/A902

E04 AUTOMATIC WATER DISTILLER - 8 GALLONS PER DAY W/ 4 GALLON RESERVE TANK - DURASTILL MODEL 301 OR APPROVED EQUAL

E05 STEAM ROOM (BY PLUMBING CONTRACTOR) EXIST CONCRETE PAD TO REMAIN

L - LABORATORY DECK-MOUNTED FITTINGS AND SINKS (COORD CONNECTIONS W/ MEP CONTRACTORS)

L01A DECK-MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X AIR SERVICE

L01G DECK-MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X GAS SERVICE

L01V DECK-MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X VACUUM SERVICE

L02A DECK-MOUNTED ELECTRICAL FIXTURE - DOUBLE-FACED, SINGLE WIDE PEDESTAL W/ GFCI RECEPTACLES, RECEPTACLES TO INCLUDE USB-A AND USB-C POWER CONNECTIONS

L02B DECK-MOUNTED ELECTRICAL FIXTURE - DOUBLE-FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES, 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS

L02C DECK-MOUNTED ELECTRICAL FIXTURE - DOUBLE-FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES, 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS. PROVIDE BLANK AT SECOND FIXTURE EACH SIDE FOR OWNER'S DATA CONNECTION

L03 DECK MOUNTED COMBINATION WATER AND GAS FITTING; FAUCET W/ 6" SPREAD GOOSENECK AND REMOVEABLE AERATOR, TWO WAY TURRET W/ GAS OUTLET EACH SIDE

L04 DECK-MOUNTED EMERGENCY EYE WASH AND DRENCH HOSE

L04A DECK-MOUNTED ACCESSIBLE EMERGENCY EYE WASH

L05 DECK-MOUNTED MIXING FAUCET

L05A DECK-MOUNTED MIXING FAUCET W/ ACCESSIBLE BLADE HANDLES

L06 INTEGRAL EPOXY RESIN CUP SINK (6" x 3" x 7.5")

L07 INTEGRAL EPOXY RESIN SINK (25" x 15" x 10")

L07A INTEGRAL EPOXY RESIN ACCESSIBLE SINK (25" x 15" x 4.5-11" HIGH/LOW)

S - SAFETY EQUIPMENT

S01 DRENCH SHOWER AND EYE WASH COMBINATION, COORD CONNECTIONS W/ PLUMBING CONTRACTOR

S01A ACCESSIBLE DRENCH SHOWER AND EYE WASH COMBINATION, COORD CONNECTIONS W/ PLUMBING CONTRACTOR


S02 FIRE BLANKET CABINET W/ FIRE BLANKET

S03 TYPE A-B-C FIRE EXTINGUISHER W/ BRACKET MOUNT

S04 GAS CYLINDER WALL BRACKET - 8L X 2'D X 4'H (1 CYLINDER CAPACITY)


**GENERAL INTERIOR / CASEWORK NOTES**

- PROVIDE STANDARD LOCKS AT ALL CABINETS UNLESS NOTED OTHERWISE, KEY ALIKE PER ROOM AND MASTER KEY FOR PROJECT.
- VERIFY EQUIPMENT SIZES, WEIGHTS, AND CLEARANCES AND ADJUST CASEWORK ACCORDINGLY.
- PROVIDE FILLER PANELS FOR ALL CASEWORK AND SCRIBE TO WALL.
- ALL COUNTERTOPS TO BE 1" EPOXY RESIN UNLESS NOTED OTHERWISE. PROVIDE 4" HIGH MATCHING EPOXY RESIN BACKSPLASH AGAINST ALL WALLS AND AS NOTED.
- REFER TO SPECIFICATIONS FOR WOOD CASEWORK SPECIES, FINISH, AND HARDWARE TYPES.
- INSTALL RB-1 RESILIENT BASE ON THE BASE OF ALL CASEWORK.
- PAPER TOWEL DISPENSERS AND SOAP DISPENSERS AT EACH SINK LOCATION TO BE FURNISHED BY THE OWNER AND INSTALLED BY THE CONTRACTOR.
- FOR CASEWORK DEPTHS NOT SHOWN IN ELEVATION, SEE A901.
- GC TO VERIFY EXACT MOUNTING LOCATIONS OF ALL ACCESSORIES IN THE FIELD WITH THE ARCHITECT PRIOR TO INSTALLATION.
- GC SHALL PROVIDE AND INSTALL ADDITIONAL FRAMING AND BLOCKING AS REQUIRED FOR ACCESSORY INSTALLATIONS IN STUD WALL AND GPBD PARTITIONS PER THE ACCESSORY MANUFACTURER'S RECOMMENDATIONS.
- PROVIDE FINISHED END PANELS WHERE EXPOSED TO VIEW.




13 ELEVATION - 1  
SCALE: 3/4" = 1'-0"


14 ELEVATION 1 - A1  
SCALE: 3/4" = 1'-0"




11 TYPICAL LAB BENCH SECTION DETAIL  
SCALE: 3/4" = 1'-0"




12 TYPICAL COUNTER EDGE PROFILE DETAIL  
SCALE: 3" = 1'-0"




1 INSTRUMENT BENCH TYPE F  
SCALE: 3/4" = 1'-0"




2 ELEVATION - LAB BENCH TYPE F  
SCALE: 3/4" = 1'-0"



3 INSTRUMENT BENCH TYPE G  
SCALE: 3/4" = 1'-0"



4 ELEVATION - LAB BENCH TYPE G  
SCALE: 3/4" = 1'-0"



5 TYP ADA SINK DETAIL  
SCALE: 3/4" = 1'-0"

5A DRAINING RACK  
SCALE: 1" = 1'-0"


EQUIPMENT AND FITTINGS LEGEND	
NOTE:	NOT ALL ITEMS APPEAR ON ALL SHEETS
E - LABORATORY EQUIPMENT	
E01	EXISTING FREESTANDING, SELF-CONTAINED NUGGET ICE MAKER - NIC
E02	UNDERCOUNTER LABORATORY GLASSWARE WASHER - LABCONCO STEAMSCRUBBER MODEL # J41101001 OR APPROVED EQUAL
E03	WALL-MOUNTED LABORATORY PEGBOARD W/ DRIP TROUGH (32"W X 30"H) - SEE SA902
E04	AUTOMATIC WATER DISTILLER - 8 GALLONS PER DAY W/ 4 GALLON RESERVE TANK - DURASTILL MODEL 301 OR APPROVED EQUAL
E05	STEAM BOILER (BY PLUMBING CONTRACTOR) EXIST CONCRETE PAD TO REMAIN
L - LABORATORY DECK-MOUNTED FITTINGS AND SINKS (COORD CONNECTIONS W/ MEP CONTRACTORS)	
L01A	DECK-MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X AIR SERVICE
L01G	DECK-MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X GAS SERVICE
L01V	DECK-MOUNTED LABORATORY BALL VALVES - 2-WAY 180 DEG. OUTLET TURRET W/ 2X VACUUM SERVICE
L02A	DECK-MOUNTED ELECTRICAL FIXTURE - DOUBLE-FACED, SINGLE WIDE PEDESTAL W/ GFCI RECEPTACLES. RECEPTACLES TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
L02B	DECK-MOUNTED ELECTRICAL FIXTURE - DOUBLE-FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES. 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS
L02C	DECK-MOUNTED ELECTRICAL FIXTURE - DOUBLE-FACED, DOUBLE WIDE PEDESTAL W/ GFCI RECEPTACLES. 1 RECEPTACLE EACH FACE TO INCLUDE USB-A AND USB-C POWER CONNECTIONS. PROVIDE BLANK 1" SECOND FIXTURE EACH SIDE FOR OWNERS DATA CONNECTION
L03	DECK MOUNTED COMBINATION WATER AND GAS FITTING. FAUCET W/ 6" SPREAD GOOSENECK AND REMOVABLE AERATOR. TWO WAY TURRET W/ GAS OUTLET EACH SIDE.
L04	DECK-MOUNTED EMERGENCY EYE WASH AND DRENCH HOSE
L04A	DECK-MOUNTED ACCESSIBLE EMERGENCY EYE WASH
L05	DECK-MOUNTED MIXING FAUCET
L05A	DECK-MOUNTED MIXING FAUCET W/ ACCESSIBLE BLADE HANDLES
L06	INTEGRAL EPOXY RESIN CLIP SINK (6" X 3" X 7.5")
L07	INTEGRAL EPOXY RESIN SINK (25" X 15" X 10")
L07A	INTEGRAL EPOXY RESIN ACCESSIBLE SINK (25" X 15" X 4.5-11" HIGH-LOW)
S - SAFETY EQUIPMENT	
S01	DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR
S01A	ACCESSIBLE DRENCH SHOWER AND EYE WASH COMBINATION. COORD CONNECTIONS W/ PLUMBING CONTRACTOR
S02	FIRE BLANKET CABINET W/ FIRE BLANKET
S03	TYPE A-B-C FIRE EXTINGUISHER W/ BRACKET MOUNT
S04	GAS CYLINDER WALL BRACKET - 8L X 2D X 4H (1 CYLINDER CAPACITY)

GENERAL INTERIOR / CASEWORK NOTES


- PROVIDE STANDARD LOCKS AT ALL CABINETS UNLESS NOTED OTHERWISE. KEY ALIKE PER ROOM AND MASTER KEY FOR PROJECT.
- VERIFY EQUIPMENT SIZES, WEIGHTS, AND CLEARANCES AND ADJUST CASEWORK ACCORDINGLY.
- PROVIDE FILLER PANELS FOR ALL CASEWORK AND SCRIBE TO WALL.
- ALL COUNTERTOPS TO BE 1" EPOXY RESIN UNLESS NOTED OTHERWISE. PROVIDE 4" HIGH MATCHING EPOXY RESIN BACKSPLASH AGAINST ALL WALLS AND AS NOTED.
- REFER TO SPECIFICATIONS FOR WOOD CASEWORK SPECIES, FINISH, AND HARDWARE TYPES.
- INSTALL RB-1 RESILIENT BASE ON THE BASE OF ALL CASEWORK.
- PAPER TOWEL DISPENSERS AND SOAP DISPENSERS AT EACH SINK LOCATION TO BE FURNISHED BY THE OWNER AND INSTALLED BY THE CONTRACTOR.
- FOR CASEWORK DEPTHS NOT SHOWN IN ELEVATION, SEE A901.
- GC TO VERIFY EXACT MOUNTING LOCATIONS OF ALL ACCESSORIES IN THE FIELD WITH THE ARCHITECT PRIOR TO INSTALLATION.
- GC SHALL PROVIDE AND INSTALL ADDITIONAL FRAMING AND BLOCKING AS REQUIRED FOR ACCESSORY INSTALLATIONS IN STUD WALL AND GPBD PARTITIONS PER THE ACCESSORY MANUFACTURER'S RECOMMENDATIONS.
- PROVIDE FINISHED END PANELS WHERE EXPOSED TO VIEW.




6 MOBILE DEMO BENCH - PLAN  
SCALE: 1" = 1'-0"




7 MOBILE DEMO BENCH - ISOMETRIC  
NOT TO SCALE



8 SECTION AT DISPLAY ABOVE MOBILE CART  
SCALE: 1" = 1'-0"



9 SECTION AT DISPLAY ABOVE CABINET  
SCALE: 1" = 1'-0"



10 SECTION AT MARKERBOARD  
SCALE: 1" = 1'-0"

































12/1/2025 2:55:36 PM Autodesk Docs: \\U04-21-01 Westmoreland CCC - Chem Lab Renovation\21-004-01\WCCC Chem Lab Renovation CENTRAL R23.rvt































































# HVAC SYMBOLS & ABBREVIATIONS






















## SHEET METAL SYMBOLS

	SUPPLY AIR DUCT TURNED UP
	SUPPLY AIR DUCT TURNED DOWN
	RETURN, EXHAUST OR RELIEF AIR DUCT TURNED UP
	RETURN, EXHAUST OR RELIEF AIR DUCT TURNED DOWN
	RETURN, EXHAUST OR RELIEF AIR DUCT PENETRATION THRU ROOF
	SUPPLY AIR DUCT PENETRATION THRU ROOF
	DIRECTION OF AIR FLOW ARROW
	RECTANGULAR DUCT. DIMENSION IS FREE AREA. REFER TO PROJECT MANUAL FOR DUCT LINER REQUIREMENTS. ADD LINER THICKNESS TO EACH DIMENSION TO GET OUTSIDE DIMENSION OF SHEET METAL. (1ST FIGURE, SIDE SHOWN; 2ND FIGURE, SIDE NOT SHOWN.)
	RECTANGULAR MAIN DUCT WITH 45° CLINCH COLLAR, AND VOLUME DAMPER IN SUB-DUCT. (PER SMACNA DUCT CONSTRUCTION STANDARDS)
	ROUND DUCT. SINGLE WALL. FOR DOUBLE WALL DUCT REQUIREMENTS, SEE SPECIFICATION AND/OR SEE CODED NOTES ON PLANS.
	ROUND MAIN DUCT WITH 90° TAP OR 90° SADDLE TAP AND VOLUME DAMPER IN SUB-DUCT. (PER SMACNA DUCT CONSTRUCTION STANDARDS)
	TRANSITIONS. GIVE SIZES. NOTE F.O.T. (FLAT ON TOP), OR F.O.B. (FLAT ON BOTTOM) IF APPLICABLE.
	ACCESS DOOR (AD) OR ACCESS PANEL (AP) AS NOTED.
	INCLINED RISE (UP) OR DROP (DN) ARROW IN DIRECTION OF AIR FLOW.
	DUCT MOUNTED SMOKE DETECTOR
	VOLUME DAMPER
	BACKDRAFT DAMPER (BDD)
	COUNTER BALANCED BACKDRAFT DAMPER (CBDD)
	AUTOMATIC AIR DAMPER
	FIRE DAMPER (FD)
	FIRE SMOKE DAMPER (FSD)
	SMOKE DAMPER (SD)
	FLEXIBLE DUCT CONNECTION TO FAN (OR EQUIP. WITH FAN)
	FLEXIBLE DUCT
	FLEXIBLE DUCT CONNECTION, WITH EQUIVALENT 90° ELBOW, TO ROUND DIFFUSER.
	FLEXIBLE DUCT OR ROUND HARD METAL DUCT CONNECTION, WITH NO 90° ELBOW, TO ROUND DIFFUSER.
	FLEXIBLE DUCT CONNECTION, WITH ONE EQUIVALENT 90° TURN OR OFFSET, TO SQUARE DIFFUSER.
	FLEXIBLE DUCT OR ROUND HARD METAL DUCT CONNECTION, WITH NO 90° ELBOW, TO SQUARE DIFFUSER.
	DIRECTION DIFFUSER (SLD). DARKENED QUADRANT(S) NO AIR FLOW. 3-WAY BLOW SHOWN.
	ROUND DUCT
	FLAT OVAL DUCT
	DIRECTION OF AIR FLOW IN OR OUT OF EQUIPMENT OR AN AIR TERMINAL DEVICE.










## PIPING SYMBOLS

	CHILLED WATER RETURN
	CHILLED WATER SUPPLY
	COLD (CITY) WATER PIPING
	COOL CONDENSATE DRAIN
	DRAIN
	NATURAL GAS PIPING
	HIGH PRESSURE STEAM RETURN
	HIGH PRESSURE STEAM
	HOT WATER RETURN
	HOT WATER SUPPLY
	LIQUID PROPANE GAS PIPING
	LOW PRESSURE STEAM RETURN
	LOW PRESSURE STEAM
	PUMPED DISCHARGE PIPING (FROM CONDENSATE PUMP)
	REFRIGERANT HOT GAS
	REFRIGERANT LIQUID
	REFRIGERANT SUCTION
	PIPING TURNED UP
	PIPING TURNED DOWN
	90° RISE OR DROP IN PIPE
	45° RISE OR DROP IN PIPE
	PIPE TAKEOFF FROM TOP OF MAIN
	PIPE TAKEOFF FROM BOTTOM OF MAIN
	PIPE TAKEOFF FROM SIDE OF MAIN
	GATE VALVE
	BALL VALVE
	GLOBE VALVE
	PLUG VALVE
	BUTTERFLY VALVE
	DRAIN VALVE WITH HOSE CONNECTION
	CHECK VALVE
	FLOW CONTROL VALVE WITH GPM INDICATED WHEN LOCATED IN MAINS OR SERVING MULTIPLE UNITS. WHEN SERVING SINGLE UNIT, REFER TO EQUIPMENT SCHEDULES.
	PRESSURE RELIEF VALVE
	PRESSURE REDUCING VALVE WITH BUILT-IN CHECK VALVE
	UNION
	TWO-WAY CONTROL VALVE
	THREE-WAY CONTROL VALVE
	AIR VENT. INSTALL AT ALL HIGH POINTS IN SYSTEM
	AAV-AUTOMATIC. MAV-MANUAL. EXTEND DRAIN LINE FROM ALL AUTOMATIC AIR VENTS TO NEAREST CONDENSATE DRAIN LINE OR SAFEWASTE.
	PRESSURE GAUGE AND COCK
	THERMOMETER
	WELL IN PIPING
	PRESSURE/TEMPERATURE TEST PORT
	HOSE BIBB
	HOSE BIBB W/CAP
	STRAINER
	STRAINER WITH BLOWDOWN AND HOSE CONNECTION (HOSE BIBB)
	STRAINER WITH BLOWDOWN, BALL VALVE WINCH & CAP.
	PIPE REDUCER
	FLEXIBLE PIPE CONNECTIONS
	DIRECTION OF PIPE SLOPE (DOWN)
	DIRECTION OF FLOW IN PIPE
	EXPANSION COMPENSATOR AND GUIDES
	PIPE ANCHOR
	FLOW SWITCH
	FLOW CONTROL VALVE
	TEST PLUG
	WATER FLOW MEASURING DEVICE

## GENERAL DRAWING SYMBOLS

	POINT OF CONNECTION - NEW TO EXISTING
	DEMOLITION LIMIT
	CODED NOTE
	EQUIPMENT TAG (REFER TO APPROPRIATE SCHEDULE)
	'D' DENOTES EQUIPMENT TYPE (I.E. EXHAUST FAN)
	'NO' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION
	'S' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION (REFER TO APPROPRIATE SCHEDULE)
	'D' DENOTES DIFFUSER, REGISTER, GRILLE TYPE (I.E. SCQ-SQUARE CONE DIFFUSER)
	'S' DENOTES NECK SIZE AND BLOW PATTERN (I.E. 12X12" - OR 12X12" NECK WITH 3-WAY BLOW PATTERN)
	'CFM' INDICATES AIR FLOW RATE IN CFM
	SECTION INDICATOR
	'D1' DENOTES SEQUENTIAL ALPHABETIC DESIGNATION BETWEEN SECTIONS
	'D2' DENOTES DRAWING ON WHICH SECTION IS LOCATED
	DETAIL INDICATOR
	'NO' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION
	'DWG' DENOTES DRAWING ON WHICH DETAIL IS LOCATED
	ELEVATION/VIEW INDICATOR
	'NO' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION
	'D' DENOTES DRAWING ON WHICH ELEVATION/VIEW IS LOCATED
	REVISION INDICATOR
	'NO' DENOTES REVISION LEVEL




## CONTROL SYMBOLS

	PILOT SWITCH (FAN CONTROL)
	VARIABLE SPEED CONTROLLER
	PUSH BUTTON CONTROLLER WITH PILOT LIGHT
	HUMIDISTAT OR HUMIDITY SENSOR
	THERMOSTAT OR TEMPERATURE SENSOR
	NIGHT THERMOSTAT
	COMBINATION SENSOR. REFER TO ATC SPEC FOR DETAILS
	CARBON DIOXIDE SENSOR
	CARBON MONOXIDE SENSOR

## GENERAL NOTES:


- UNLESS CONDITIONS DO NOT PERMIT, ALL RECTANGULAR ELBOWS SHALL BE THE RADIUS TYPE USED. WHERE CONDITIONS DO NOT PERMIT, MITERED RECTANGULAR ELBOWS WITH TURNING VANES MAY BE PROVIDED IN LIEU OF RADIUS ELBOWS. THE RADIUS RECTANGULAR ELBOWS SHALL HAVE A RADIUS HELL AND A RADIUS THROAT, AND SHALL HAVE A CENTERLINE RADIUS NOT LESS THAN 1.5 TIMES THE DUCT WIDTH.
- ALL MITERED RECTANGULAR DUCT ELBOWS HAVING AN ANGLE GREATER THAN 45° SHALL BE PROVIDED WITH TURNING VANES.
- DUCTWORK SHALL NOT BE INSTALLED ABOVE ELECTRICAL PANELS. COORDINATE DUCTWORK WITH ELECTRICAL CONTRACTOR.
- FINAL THERMOSTAT, SENSOR, AND EXHAUST FAN SWITCH LOCATIONS MUST BE APPROVED BY THE ARCHITECT AND OWNER PRIOR TO INSTALLATION.
- DUCT DETECTORS SHALL BE PROVIDED BY THE E.C. AND MOUNTED BY THE H.C. THE E.C. SHALL PROVIDE ALL POWER WIRING AND FIRE ALARM CONTROL WIRING FOR THE DETECTOR. THE H.C. SHALL PROVIDE ALL FAN SHUTDOWN CONTROL WIRING.
- REFERENCES MADE TO THE CONTRACTOR, THE HEATING CONTRACTOR, THE HVAC CONTRACTOR, AND THE MECHANICAL CONTRACTOR SHALL MEAN ONE AND THE SAME.
- PRIOR TO THE COMMENCEMENT OF WORK, THE CONTRACTOR SHALL MEASURE AIR AND WATER FLOW RATES ON THE EXISTING AIR AND WATER SYSTEMS AND EQUIPMENT MODIFIED UNDER THIS PROJECT. SUBMIT BALANCE REPORT FOR REVIEW.
- NOTE: THE DATA OBTAINED FROM THIS PRE-CONSTRUCTION AIR AND WATER BALANCE SHALL BE USED TO BALANCE THE AIR AND WATER SYSTEMS AT THE CONCLUSION OF EACH PHASE OF CONSTRUCTION WORK.

## DEMOLITION PLAN SYMBOLS


	EXISTING DUCT TO BE REMOVED
	EXISTING EQUIPMENT TO BE REMOVED
	EXISTING DUCT OR PIPE TO BE REMOVED

## ABBREVIATIONS

AAD	AUTOMATIC AIR DAMPER	HWR	HOT WATER RETURN
AAV	AUTOMATIC AIR VENT	HWS	HOT WATER SUPPLY
ABV	ABOVE	IDF	INDUCED DRAFT FAN
ACC	AIR COOLED CHILLER	IEER	INTEGRATED ENERGY EFFICIENCY RATIO
ACU	AIR CONDITIONING UNIT	IMC	INTERNATIONAL MECHANICAL CODE
AD	ACCESS DOOR	IN	INCH
ADC	AIR DIFFUSION COUNCIL	IPLV	INTEGRATED PART LOAD VALUE
ADJ.	ADJACENT	IWG	INCHES WATER GAUGE
AFF	ABOVE FINISHED FLOOR	JSD	JET SLOT DIFFUSER
AGA	AMERICAN GAS ASSOCIATION	KH	KITCHEN HOOD
AHU	AIR HANDLING UNIT	KSU	KITCHEN SUPPLY UNIT
ALT	ALTERNATE	KW	KILOWATT
AMCA	AIR MOVEMENT AND CONTROL ASSOCIATION	L	LOUVER OR LIQUID (REFRIGERANT)
AP	ACCESS PANEL	LAT	LEAVING AIR TEMPERATURE (°F)
A.P.D.	AIR PRESSURE DROP	LSG	LINEAR BAR GRILLE
ARI	AIR-CONDITIONING AND REFRIGERATION INSTITUTE	LBS	POUNDS
AS	AIR SEPARATOR	LFD	LAMINAR FLOW DIFFUSER
ASHRAE	AMERICAN SOCIETY OF HEATING, REFRIGERATING AND AIR-CONDITIONING ENGINEERS	LH	LAS HOOD
ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS	LRG	LOUVERED RETURN GRILLE
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS	LRR	LOUVERED RETURN REGISTER
ATC	AUTOMATIC TEMPERATURE CONTROL	LSO	LINEAR SLOT DIFFUSER
B	BOILER	LSR	LINEAR SLOT RETURN
BAS	BUILDING AUTOMATION SYSTEM	LW	LEAVING WATER TEMPERATURE
BCU	BLOWER COIL UNIT	MANUF	MANUFACTURER
BDD	BACK-DRAFT DAMPER	MAV	MANUAL AIR VENT
BFP	BACK-FLOW PREVENTER	MAX	MAXIMUM
BFV	BUTTERFLY VALVE	MBH	1000 BTUH
BHP	BREAK HORSE POWER	MCA	MINIMUM CIRCUIT AMPS
BJ	BETWEEN JOISTS	MIN	MINIMUM
BL STL	BLACK STEEL	MOCPP	MAXIMUM OVER CURRENT PROTECTION
BLDG	BUILDING	MTD	MOUNTED
BTUH	BRITISH THERMAL UNITS/HOUR	NC	NOISE COEFFICIENT
BV	BALL VALVE	N.C.	NORMALLY CLOSED
C	CHILLER	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
CAU	COMBUSTION AIR UNIT	N.O.	NORMALLY OPEN
CAV	CONSTANT AIR VOLUME	NO.	NUMBER
CBDD	COUNTER BALANCED BACKDRAFT DAMPER	NPLV	NON-STANDARD PART LOAD VALUE
CD	COIL CONDENSATE DRAIN OR CEILING DIFFUSER	NPW	NON POTABLE WATER
CFM	CUBIC FEET PER MINUTE	OA	OUTSIDE AIR
CHWR	CHILLED WATER RETURN	OAI	OUTSIDE AIR INTAKE
CHWS	CHILLED WATER SUPPLY	OAT	OUTSIDE AIR TEMPERATURE (°F)
CLG	CEILING	OBD	OPPOSED BLADE DAMPER
CO	CLEAN OUT	OCC	OCCUPANCY
CONN	CONNECTION	OSBY	OUTSIDE STEM AND YOKE GATE VALVE
CP	CONTROL PANEL	P	PUMP
CRAC	COMPUTER ROOM AIR CONDITIONING UNIT	PC	PLUMBING CONTRACTOR
CS	CIRCUIT SETTER	PD	PRESSURE DROP OR PUMPED DISCHARGE
CU	CONDENSING UNIT	PDU	POOL DEHUMIDIFICATION UNIT
CUH	CABINET UNIT HEATER	PG	PRESSURE GAUGE OR PROPYLENE GLYCOL
CV	HOT WATER CONVECTOR	PH	PHASE
DW	COLD WATER OR CITY WATER	PRV	PRESSURE RELIEF VALVE
DB	DRY BULB	PRS	PRESSURE REDUCING STATION
dB	DECIBEL	PSI	POUNDS PER SQUARE INCH
DC	DUST COLLECTOR	PIT	PRESSURE/TEMPERATURE PORT
DOW	DOMESTIC COLD WATER	PTAC	PACKAGED TERMINAL AIR CONDITIONER
F	DEGREE FAHRENHEIT	PV	PLUG VALVE
DD	DUCT MOUNTED SMOKE DETECTOR	RA	RETURN AIR
DG	DOUBLE DEFLECTION GRILLE	RAD.	RADIATED (SOUND)
DEMO	DEMOLITION	RAT	RETURN AIR TEMPERATURE (°F)
DF	DUCT FURNACE (GAS FIRED)	RCD	ROUND CONE DIFFUSER
DL	DRUM LOUVER	RCP	RADIANT CEILING PANEL (HOT WATER)
DSCH.	DISCHARGE	REFRIG	REFRIGERANT
DTR	DUAL TEMPERATURE RETURN	REGEN	REGENERATE
DTS	DUAL TEMPERATURE SUPPLY	RG	RETURN GRILLE
DX	DIRECT EXPANSION	RH	RELATIVE HUMIDITY
EAT	ENTERING AIR TEMPERATURE (°F)	RL	REFRIGERANT LIQUID
EC	ELECTRICAL CONTRACTOR	RMA	RELIEF AIR ROOM
ECC	ECC CRATE GRILLE	RPM	REVOLUTIONS PER MINUTE
ECH	ELECTRIC CEILING HEATER	RR	RETURN REGISTER
EDUH	ELECTRIC CABINET UNIT HEATER	RRT	REFRIGERANT SUCTION
EDC	ELECTRIC DUCT COIL	RTU	ROOFTOP UNIT
EER	ENERGY EFFICIENCY RATIO	RV	ROOF VENTILATOR
EF	EXHAUST FAN	S	SUCTION (REFRIGERANT)
EG	EXHAUST GRILLE OR ETHYLENE GLYCOL	S.A.	SOUND ATTENUATOR
EJ	EXPANSION JOINT	SA	SUPPLY AIR
ER	EXHAUST REGISTER	SAN	SANITARY
ERP	ELECTRIC RADIANT CEILING PANEL	SAT	SUPPLY AIR TEMPERATURE (°F)
ERV	ENERGY RECOVERY VENTILATOR	SCOR	SHORT CIRCUIT CURRENT RATING
E.S.P.	EXTERNAL STATIC PRESSURE	SCD	SQUARE CONE DIFFUSER (4-WAY BLOW PATTERN)
ET	EXPANSION TANK ELECTRIC	SD	SMOKE DAMPER
EUH	ELECTRIC UNIT HEATER	SDG	SPIRAL DUCT GRILLE
EWH	ELECTRIC WALL HEATER	SENS.	SENSIBLE
EWT	ENTERING WATER TEMPERATURE	SF	SUPPLY FAN
EXP	EXPANSION	SFC	SPLIT FAN COIL UNIT
FD	FIRE DAMPER	SG	SUPPLY GRILLE
FSD	FIRE AND SMOKE DAMPER	SLD	SQUARE DIRECTIONAL DIFFUSER
FC	FLUID COOLER	SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTORS' NATIONAL ASSOCIATION
FDU	FAN COIL UNIT	SMR	SNOWMELT RETURN
FLA	FULL LOAD AMPS	SMS	SNOWMELT SUPPLY
FLEX	FLEXIBLE	SFD	SQUARE FLANGE DIFFUSER
FLD	FLAT DUAL DUCTWORK	SQ	SQUARE
FOT	FLAT ON TOP	SR	SUPPLY REGISTER
FPB	FAN POWERED BOX	ST STL	STAINLESS STEEL
FFI	FMS PER INCH	T	THERMOSTAT OR THERMOMETER
FT	FEET	TB	TERMINAL BOX
FTR	FINNED TUBE RADIATION	TDF	T-BAR DIFFUSER
FURN	FURNISH	TDV	TRIPLE DUTY VALVE
G	GAS (NATURAL OR REFRIGERANT)	TFD-x	TRANSFER DUCT - SIZE PER DETAIL
GA	GAUGE	TJ	THREAD JOISTS
GAL	GALLON	T.P.	TOTAL PRESSURE
GC	GENERAL CONTRACTOR	TPD	THERMALLY POWERED DIFFUSER
GLYCOL	GLYCOL FEED UNIT	T.S.P.	TOTAL STATIC PRESSURE
GMRU	GROUND MOUNTED ROOFTOP UNIT	T STAT	THERMOSTAT
GPM	GALLONS PER MINUTE	TYP	TYPICAL
GRV	GRAVITY ROOF VENTILATOR	UH	UNIT HEATER
GUH	GAS FIRED UNIT HEATER	UV	UNIT VENTILATOR
GV	GATE VALVE	V	VOLTAGE
H	HUMIDISTAT	VAV	VARIABLE AIR VOLUME
HB	DRAIN VALVE WITH HOSE CONNECTION (HOSE BIBB)	VAVD	VARIABLE AIR VOLUME DIFFUSER
HC	HVAC CONTRACTOR	VEL	VELOCITY
HD	KITCHEN/LAB HOOD	VFD	VARIABLE FREQUENCY DRIVE
HDGG	HEAVY DUTY GYM GRILLE	VOC	VOLATILE ORGANIC COMPOUNDS
HI	HYDRONICS INSTITUTE	VOLD	VOLUME DAMPER
HP	HORSEPOWER OR HEAT PUMP	WB	WET BULB
HR	HOUR OR HUMIDITY RATIO	WCC	WATER COOLED CHILLER
HRU	HEAT RECOVERY UNIT	WG	WATER GAUGE
HTX	HEAT EXCHANGER	W.P.D.	WATER PRESSURE DROP
HU	HUMIDIFIER	WSPH	WATER SOURCE HEAT PUMP
HVAC	HEATING, VENTILATING & AIR CONDITIONING	x	EXISTING
HU1	HEATING AND VENTILATING UNIT	XCD	EXISTING CONDENSATE DRAIN



**1** HVAC FIRST FLOOR DEMO  
H101 SCALE: 1/8" = 1'-0"



**2** HVAC FIRST FLOOR NEW WORK  
H101 SCALE: 1/8" = 1'-0"

- CODED NOTES\_H101**
- 1 REMOVE EXHAUST FAN ON ROOF ABOVE. DISCONNECT POWER WIRING AND CONTROL WIRING. EXISTING CURB TO REMAIN. REMOVE EXISTING BACKDRAFT DAMPER IN DUCTWORK.
  - 2 REMOVE DUCT DROP DOWN TO FUME HOOD. REMOVE ANY STORAGE CABINET VENT PIPES AND PATCH DUCT AS NEEDED.
  - 3 REMOVE EXHAUST FAN. DISCONNECT POWER WIRING AND CONTROL WIRING. EXISTING CURB TO REMAIN. REMOVE DUCT DROP DOWN TO FUME HOOD. REMOVE ANY STORAGE CABINET VENT PIPES AND PATCH.
  - 4 REMOVE SMOKE DUCTWORK BACK TO WHERE IT CONNECTS TO THE MAIN. PATCH MAIN DUCTWORK.
  - 5 REMOVE SLOT DIFFUSERS AND BAFFLE COVERS TO ACCOMMODATE NEW FUME HOOD INSTALLATION. RETAIN AND REINSTALL DIFFUSERS AND BAFFLES AFTER THE FUME HOOD IS INSTALLED.
  - 6 PROVIDE NEW EXHAUST FAN. MOUNT FAN TO EXISTING CURB USING ADAPTER CURB. CONNECT CONTROL WIRING FOR FAN TO FAN SWITCH LOCATED ON FACE OF FUME HOOD. PROVIDE NEW MOTORIZED DAMPER IN THE SAME LOCATION AS THE PREVIOUSLY REMOVED BACKDRAFT DAMPER.
  - 7 FUME HOOD FACE VELOCITY MONITOR PROVIDED BY OTHERS. BALANCE HOODS TO THE MANUFACTURERS INDICATED AIRFLOW AT 18" SASH POSITION.
  - 8 12"Ø DUCT DOWN AND CONNECT TO FUME HOOD. TRANSITION AND OFFSET AS REQUIRED.


UNIT NO.	AREA SERVED	TYPE	TOTAL AIRFLOW (CFM)	FAN RPM	E.S.P. (IN WG)	MOTOR					CONTROL	INLET dBA (dB)	BASED ON		REMARKS
						RPM	HP	BHP	V	P			MANUF.	MODEL	
EF-1	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-2	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-3	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-4	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-5	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-6	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-7	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-8	ORGANIC CHEM LAB 3401	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-9	ORGANIC CHEM LAB 3401	UPBLAST - BELT	950	1577	0.75	1725	1/3	0.27	120	1	SWITCH	58	GREENHECK	CUBE-100	1 - 4
EF-10	ORGANIC CHEM STOR 3402	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-11	INSTRUMENT ROOM 3403	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-12	INORGANIC CHEM LAB 3400	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-13	INORGANIC CHEM LAB 3400	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-14	INORGANIC CHEM LAB 3400	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-15	INORGANIC CHEM STOR 3404	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-16	INORGANIC CHEM STOR 3404	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-17	INORGANIC CHEM LAB 3308	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-18	INORGANIC CHEM LAB 3308	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4
EF-19	INORGANIC CHEM LAB 3308	UPBLAST - BELT	785	1671	0.75	1725	1/4	0.23	120	1	SWITCH	60	GREENHECK	CUBE-099	1 - 4

- REMARKS:**
1. INTEGRAL DISCONNECT.
  2. MOTORIZED DAMPER.
  3. ADAPTER CURB.
  4. EXPLOSION PROOF MOTOR AND SPARK PROOF FAN.











1 PLUMBING FIRST FLOOR NEW WORK PLAN  
P101 SCALE: 1/4" = 1'-0"

GENERAL NOTES (THIS SHEET)

A. REFER TO ALL ARCHITECTURAL DRAWINGS, ELEVATION PLANS & SPECIFICATIONS FOR PLUMBING CONNECTION REQUIREMENTS TO EACH LAB TABLE, FUME HOOD AND EACH PIECE OF LAB EQUIPMENT.

CODED NOTES SHEET P101

- EXISTING PLUMBING PIPING AND ASSOCIATED VALVES, FITTINGS, ETC. TO REMAIN.
- CONNECT NEW PLUMBING PIPING INTO EXISTING PLUMBING PIPING IN THIS AREA. FIELD VERIFY EXACT CONNECTION LOCATION AND INVERT AND MATCH EXISTING SIZE.
- NEW FUME HOOD TO BE PROVIDED BY G.C. EXTEND NEW VAC, CW, & G PIPING DOWN INTO FUME HOOD AND MAKE THE FINAL CONNECTIONS REQUIRED. CONNECT HOOD SINK INTO EXISTING SANITARY PIPING. COORDINATE WITH G.C. IN FIELD.
- NEW FUME HOOD TO BE PROVIDED BY G.C. EXTEND NEW AIR, VAC, & G PIPING DOWN INTO FUME HOOD AND MAKE THE FINAL CONNECTIONS REQUIRED. CONNECT HOOD SINK INTO EXISTING SANITARY PIPING. COORDINATE WITH G.C. IN FIELD.
- NEW FUME HOOD TO BE PROVIDED BY G.C. EXTEND NEW AIR, VAC, CW, G, AND STEAM PIPING DOWN INTO FUME HOOD AND MAKE THE FINAL CONNECTIONS REQUIRED. CONNECT HOOD SINK INTO EXISTING SANITARY PIPING. COORDINATE WITH G.C. IN FIELD.
- EXISTING FLOOR DRAIN/CLEANOUT TO REMAIN.
- NEW STEAM BOILER BY P.C. PROVIDE ALL NEW BRANCH PIPING, VALVES, FITTINGS, ETC. AND CONNECT BACK INTO THE EXISTING PIPING. INSTALL NEW BOILER ONTO EXISTING CONCRETE PAD. MODIFY PAD, IF REQUIRED.
- NEW SINK TO BE PROVIDED BY G.C. CONNECT NEW BRANCH PIPING INTO EXISTING PLUMBING ROUGH-INS. COORDINATE WITH G.C. IN FIELD.
- EXISTING WALL HYDRANT TO REMAIN.
- CONNECT NEW 1-1/2" HW LINE INTO EXISTING HW LINE ABOVE CORRIDOR CEILING. FIELD VERIFY EXACT CONNECTION LOCATION AND INVERT.
- CONNECT NEW 3/4" HR LINE INTO EXISTING HR LINE ABOVE CORRIDOR CEILING. FIELD VERIFY EXACT CONNECTION LOCATION AND INVERT. PROVIDE A CHECK VALVE, BALL VALVE AND BALANCING VALVE ON THIS LINE AND UPSTREAM OF THE LINE YOU ARE CONNECTING INTO.
- NEW DISTILLER TO BE PROVIDED BY OTHERS IN APPROXIMATELY THIS LOCATION. EXTEND EXISTING CW LINE AND MAKE FINAL CONNECTION.
- NEW 1/2" HW LINE DOWN IN CHASE TO SERVE SINKS.
- CAP STEAM PIPING ABOVE CEILING.
- 1/2" CW DOWN TO ICEMAKER OUTLET BOX. COORDINATE EXACT LOCATION WITH OWNER AND MAKE FINISHED CONNECTIONS TO ICEMAKER.
- 1/2" HW DOWN TO NEW DISHWASHER. ROUTE DRAIN LINE OVER TO SINK TRAP.
- CAP AIR PIPING ABOVE CEILING.
- NEW EYEWASH BY G.C. ROUTE NEW 1/2" CW AND HW PIPING TO EMERGENCY MIXING VALVE IN CABINETRY AND ROUTE 1/2" TEMPERED WATER LINE OVER TO EYEWASH.
- ADD SHUT-OFF VALVES TO EXISTING LINES TO ASSIST WITH PHASING OF THE WORK AREAS.
- NEW LAB TABLE AND SINK TO BE PROVIDED BY G.C. DROP 3/4" CW, 3/4" HW, 1-1/4" VAC, 3/4" G & 1-1/2" V PIPING DOWN IN COLUMN INTO CASEWORK AND ROUTE TO ALL OUTLETS, TURRETS AND SINK REQUIRING PLUMBING CONNECTIONS. CONNECT SINK INTO EXISTING SANITARY PIPING. COORDINATE WITH G.C. IN FIELD.
- NEW LAB TABLE AND SINK TO BE PROVIDED BY G.C. DROP 3/4" CW, 3/4" HW, 3/4" AIR, 1-1/4" VAC, 3/4" G & 1-1/2" V PIPING DOWN IN COLUMN INTO CASEWORK AND ROUTE TO ALL OUTLETS, TURRETS AND SINK REQUIRING PLUMBING CONNECTIONS. CONNECT SINK INTO EXISTING SANITARY PIPING. COORDINATE WITH G.C. IN FIELD.
- NEW COMBINATION SAFETY SHOWER/EYEWASH BY G.C. ROUTE EXISTING 1" CW AND NEW 1" HW PIPING TO EMERGENCY MIXING VALVE IN CEILING AND DROP 1-1/4" TEMPERED WATER LINE DOWN TO COMBINATION SAFETY SHOWER/EYEWASH.



C:\Revit\Local Files\Elec\Tech\_202161\_1\WCCC-Science Lab Renovation\_2023\_sbsk07MYCC.rvt

# ELECTRICAL SYMBOL LEGEND

## ELECTRICAL GENERAL NOTES

- A. BRANCH CIRCUITING:**
- ALL ELECTRICAL DEVICES HAVE BRANCH CIRCUIT NUMBERS AND PANELS INDICATED ADJACENT TO THE POWER CONNECTION SYMBOL ON THE PLANS. ALTHOUGH THE INTERCONNECTING BRANCH CIRCUITING IS NOT SHOWN, THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR ALL WIRE AND CONDUIT REQUIRED FOR A COMPLETE AND OPERATION POWER DISTRIBUTION SYSTEM.
  - UNLESS NOTED OTHERWISE ON THE DRAWINGS, ALL BRANCH CIRCUITING SHALL BE INSTALLED CONCEALED IN EMT, 3/4" MINIMUM.
  - ALL CONDUIT SHALL BE 3/4" EMT, UNLESS NOTED OTHERWISE ON THE DRAWINGS.
  - ALL BRANCH CIRCUIT WIRING SHALL BE #12AWG THIN COPPER, UNLESS NOTED OTHERWISE ON THE DRAWINGS.
  - THE MAXIMUM NUMBER OF CURRENT CARRYING WIRES DOES NOT INCLUDE GROUND WIRE IN ANY ONE CONDUIT SHALL NOT EXCEED SIX (6), UNLESS NOTED OTHERWISE ON THE DRAWINGS.
- B. GROUNDING:**
- PROVIDE A SEPARATE INSULATED GROUND WIRE IN EACH CONDUIT RUN. MINIMUM WIRE SIZE SHALL BE #12AWG. GROUND WIRE IS TYPICALLY NOT SHOWN.
- C. LOCATION OF ALL EQUIPMENT AND DEVICES:**
- OBTAIN WRITTEN APPROVAL OF LOCATIONS OF ALL ELECTRICAL DEVICES FROM THE OWNER AND THE ARCHITECT PRIOR TO ROUGH-IN. THE OWNER RESERVES THE RIGHT TO MOVE ANY OR ALL ELECTRICAL DEVICES PRIOR TO ROUGH-IN AT NO ADDITIONAL COST.
  - COORDINATE THE LOCATION AND SERVICE REQUIREMENTS OF ALL HVAC AND PLUMBING EQUIPMENT WITH THE RESPECTIVE CONTRACTORS. INFORM THE ARCHITECT OF ANY CONFLICTS IMMEDIATELY.
  - THE ELECTRICAL CONTRACTOR SHALL CHECK ALL ARCHITECTURAL, HVAC, AND PLUMBING DRAWINGS FOR THE LOCATION OF SINKS. RECEPTACLES SHALL BE LOCATED A MINIMUM OF 1'-0" FROM THE EDGE OF ANY SINK, EVEN IF SHOWN CLOSER TO THE SINK ON THE ELECTRICAL DRAWINGS.
- D. EQUIPMENT LABELING:**
- UNDER ALTERNATE BID, PROVIDE NAMEPLATE LABELS ON ALL ELECTRICAL DISTRIBUTION EQUIPMENT IN ACCORDANCE WITH DETAIL 2E100.
  - PROVIDE ARC FLASH HAZARD LABELING ON ALL ELECTRICAL DISTRIBUTION EQUIPMENT IN ACCORDANCE WITH SPECIFICATION SECTION 260573.
- E. LIGHTING FIXTURE SCHEDULE:**
- REFERENCE SPECIFICATION SECTIONS 2605100 (INTERIOR LIGHTING) FOR DETAILED LAMP, DRIVER AND FIXTURE SPECIFICATIONS.
  - BID PRICES SHALL BE BASED ON INFORMATION IN ALL COLLUMS. WHERE A CONFLICT EXISTS, THE PRICE SHALL INCLUDE THE MORE EXTENSIVE OPTION. COORDINATE CONFLICTS WITH ENGINEER PRIOR TO SUBMITTING BID.
  - THE FIXTURE MANUFACTURER SHALL BE RESPONSIBLE FOR THE LAMP/DRIVER COMPATIBILITY.
  - NOMINAL LUMEN OUTPUT IS LISTED FOR LED FIXTURE TYPES. SUBMITTED FIXTURE SHALL BE CAPABLE OF PROVIDING LISTED LUMEN OUTPUT WITHIN 10% OF RESP. LISTED LUMEN OUTPUT.
  - NO SUBSTITUTIONS SHALL BE ACCEPTED UNLESS LISTED.
  - PRICING FOR LIGHT FIXTURE TYPES SHALL BE THROUGH LOCAL LIGHTING REP LISTED ONLY.
- F. SWITCHING:**
- CHECK ALL DRAWINGS FOR WALL SWITCHES. SWITCHES ARE SHOWN ON LIGHTING, POWER, AND SYSTEM PLANS.
  - WHERE ONE OR MORE WALL SWITCHES APPEAR IN THE SAME GENERAL LOCATION, SWITCHES SHALL BE GROUPED AND INSTALLED IN ONE WALL BOX WITH ONE CONTROLS COMMON COVER PLATE. WHEREVER POSSIBLE, WHERE GROUPING IS NOT POSSIBLE DUE TO SIZE OR TYPE OF DEVICE, GROUP DEVICES CLOSE TOGETHER AND AT THE EXACT SAME MOUNTING HEIGHT.
  - ALL SWITCHES SHALL BE INSTALLED SUCH THAT ALL TOGGLES ARE IN THE DOWN POSITION WHERE THE LIGHTS THEY CONTROL ARE OFF.
- G. CUTTING AND PATCHING:**
- ALL OPENINGS IN EXISTING STRUCTURAL ELEMENTS, REQUIRED FOR COMPLETION OF THE CONTRACT (SUCH AS FLOORS, WALLS, CEILINGS, AND ROOFS), SHALL BE CUT AND/OR PATCHED BY THE ELECTRICAL CONTRACTOR.
- H. EXISTING FIRE ALARM SYSTEM:**
- THE EXISTING FIRE ALARM SYSTEM (SIMPLEX 4100ES) SHALL REMAIN AND RELOCATED AND NEW DEVICES SHOWN ON DRAWINGS SHALL BE CONNECTED TO THE EXISTING FIRE ALARM SYSTEM. PROVIDE ALL CONNECTIONS REQUIRED TO INTEGRATE NEW DEVICES TO THE EXISTING SYSTEM. PROVIDE A MINIMUM OF 4 HOURS OF TECHNICIAN LABOR FROM LOCAL MANUFACTURERS REPRESENTATIVE TO CONNECT DEVICES AND PROGRAM DEVICES INTO SYSTEM.
- I. EXISTING PANELBOARD SCHEDULES:**
- THE ELECTRICAL CONTRACTOR SHALL PROVIDE TYPE-WRITTEN PANELBOARD DIRECTORIES IN ALL EXISTING PANELBOARDS WHERE CIRCUITS HAVE BEEN ADDED OR DELETED. THE INFORMATION FOR EACH CIRCUIT SHALL INCLUDE TYPE OF LOAD AND LOCATION OF CIRCUITING. THE ROOM NUMBERS USED TO CREATE THESE PANELBOARD DIRECTORIES WILL BE BASED ON THE AS-BUILT ROOM NUMBERS, IF DIFFERENT THAN THE ROOM NUMBERS ON DRAWINGS. COORDINATE THE ROOM NUMBERS WITH OWNER AND ARCHITECT PRIOR TO CREATING DIRECTORIES. AFTER ALL DIRECTORIES HAVE BEEN INSTALLED IN PANELBOARDS, THE CONTRACTOR WILL PROVIDE ALL DIRECTORIES ON A FLASH DRIVE LISTING SOFTWARE USED TO CREATE THE FILES FOR USE BY THE OWNER.
- J. EXISTING CIRCUIT NUMBERS:**
- THE CIRCUIT NUMBERS SHOWN ON THE DRAWINGS ARE BASED ON THE ORIGINAL CONTRACT DOCUMENTS AND EXISTING PANELBOARD SCHEDULES. THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL CIRCUIT NUMBERS IN FIELD PRIOR COMMENCING WORK.

## GENERAL ABBREVIATIONS

A	AMPERE	NA	NOT APPLICABLE
AC	ABOVE COUNTER	NA	NOT IN THIS CONTRACT
AFF	ABOVE FINISHED FLOOR	NO	NUMBER
AWG	AMERICAN WIRE GAUGE	NTS	NOT TO SCALE
C	CONDUIT	OC	ON CENTER
CB	CIRCUIT BREAKER	OEM	ORIGINAL EQUIPMENT MANUFACTURER
CKT	CIRCUIT	P	POLE
CLG	CEILING	PB	PUSH BUTTON
CONN	CONNECTION	PH	PHASE
CU	COPPER	PNL	PANELBOARD
DISC	DISCONNECT	POS	POSITION
DWG	DRAWING	PR1	PRIMARY
E	EMERGENCY OR EMERGENCY SYSTEM	PWR	POWER
EMT	ELECTRIC METALLIC TUBING	REC	RECESSED
EQUIP	EQUIPMENT	RECPT	RECEPTACLE
EX	EXISTING	REQ	REQUIRED
FA	FIRE ALARM	RMC	RIGID GALVANIZED METAL CONDUIT
FBO	FURNISHED BY OTHERS WITH ALL RELATED ELECTRICAL WORK BY ELECTRICAL CONTRACTOR	REQ	REQUIRED
FOR	FEDER	SCOR	SHORT CIRCUIT CURRENT RATING
FH	FUME HOOD	SEC	SECONDARY
FT	FEET	SM	SURFACE MOUNTED
FTL	FEED THROUGH LUIGS	SPD	SURGE PROTECTIVE DEVICE
GND	GROUND OR GROUNDED	TYP	TYPICAL
GRD	GROUND OR GROUNDED	UNO	UNLESS NOTED OTHERWISE
HP	HORSEPOWER	V	VOLT
HVAC	HEATING, VENTILATING AND AIR CONDITIONING	W	WATT
IN	INCH	WI	WITH
JB	JUNCTION BOX	W/O	WITHOUT
KW	KILOWATT	X	EXISTING TO REMAIN
KTG	LIGHTING	XA	EXISTING TO BE REMOVED COMPLETELY
MCB	MAIN CIRCUIT BREAKER	XR	RELOCATED EXISTING EQUIPMENT
MFR	MANUFACTURER	XRN	EXISTING TO BE REMOVED AND REPLACED WITH NEW DEVICE
MLO	MAIN LUG ONLY	Y	EXISTING TO BE REMOVED AND RELOCATED
MTD	MOUNTED	YR	STAR OR WYE DISTRIBUTION SYSTEM
MTG	MOUNTING		


## CONTRACTOR ABBREVIATIONS

EC	ELECTRICAL CONTRACTOR	HC	HVAC CONTRACTOR
GC	GENERAL CONTRACTOR	PC	PLUMBING CONTRACTOR


## GENERAL DRAWING SYMBOLS

- (A) DETAIL INDICATOR. 'W' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION. 'DWG' DENOTES DRAWING NUMBER WHERE DETAIL IS DRAWN.
- (#) COLUMN LINE OR GRID INDICATOR. 'W' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION.
- (R) REVISION INDICATOR. 'W' DENOTES REVISION LEVEL.
- (B) CODED NOTE. 'W' DENOTES SEQUENTIAL ALPHANUMERIC DESIGNATION.


## LIGHTING




## LIGHTING CONTROLS




## POWER




## FIRE ALARM SYSTEM




## TELE/DATA COMMUNICATION SYSTEM (ROUGH-IN)




### 1 VOICE/DATA OUTLET ROUGH-IN REQUIREMENTS NOT TO SCALE



### 3 EQUIPMENT CONNECTION (Integral Disconnect) NOT TO SCALE





### 4 EQUIPMENT CONNECTION (Fused Disconnect Switch) NOT TO SCALE



- NOTES:**
- NAMEPLATE SHALL BE 5" WIDE BY 2-1/2" HIGH.
  - EQUIPMENT NAME SHALL BE 1/4" TALL.
  - ALL OTHER TEXT SHALL BE 1/8" TALL.
  - WHERE PANELBOARD IS LOCATED IN AN ELECTRICAL/MECHANICAL ROOM, INSTALL NAMEPLATE ON FACE OF PANELBOARD AND SECURE NAMEPLATE TO EQUIPMENT WITH TWO SHEET METAL SCREWS.
  - WHERE PANELBOARD IS LOCATED IN AN OCCUPIED SPACE OR CORRIDOR, INSTALL NAMEPLATE ON INSIDE OF DOOR AND SECURE NAMEPLATE TO EQUIPMENT WITH DOUBLE-SIDED TAPE. PROVIDE SECOND NAMEPLATE ON FACE OF PANELBOARD WITH PANELBOARD NAME ONLY SECURED WITH TWO METAL SCREWS. SECOND NAMEPLATE SHALL BE 3/4" HIGH WITH 1/2" TALL TEXT.
- 2 NAMEPLATE DETAIL - PANELBOARDS NOT TO SCALE


LIGHTING FIXTURE SCHEDULE											
TAG	GENERAL	COLOR	MOUNTING	LUMEN OUTPUT	LOAD	VOLTAGE	MANUFACTURER / MODEL SERIES				
							LAFACE & MCGOVERN	REPCO II	ARCHITECTURAL LIGHTING SALES	PAOLICELLI ONE/SOURCE	GORMLEY FARRINGTON
EMERGENCY LIGHTING FIXTURES											
E01	BATTERY PACK, DUAL LAMP, THERMOPLASTIC HOUSING	WHITE	SURFACE	LED 1500 LUMENS	10.6W	120/277	LITHONIX EM6L	CHLORIDE TPU LM7	EXTRONIX NFK-HO	DUAL LITE EVHC12	LIGHTALARMS LCA-2RH
EXISTING LIGHT FIXTURES											
X01	EXISTING 24 TROFFER, FLAT PANEL	WHITE	RECESSED								





**CODED NOTES - ELECTRICAL DEMOLITION PLAN - LIGHTING**

1. UNLESS NOTED OTHERWISE, EXISTING LIGHT FIXTURES, SWITCHES, AND ALL ASSOCIATED WIRING IN THIS ROOM TO REMAIN.
2. UNLESS NOTED OTHERWISE, EXISTING LIGHT FIXTURES IN THIS ROOM TO REMAIN. REVISE SWITCHES AND ASSOCIATED WIRING AS SHOWN ON NEW WORK PLAN.
3. REMOVE EXISTING EMERGENCY BATTERY UNIT AND REPLACE WITH NEW AS SHOWN ON NEW WORK PLAN. EXISTING WIRING TO REMAIN FOR RECONNECTION TO NEW FIXTURE.
4. REMOVE EXISTING LIGHT SWITCH AT THIS LOCATION THAT IS CURRENTLY NOT CONTROLLING ANYTHING. PROVIDE NEW COVERPLATE ON DOUBLE-GANG JUNCTION BOX WITH SINGLE OPENING FOR THE ONE ACTIVE SWITCH.
5. REMOVE BOTH SWITCHES AT THIS LOCATION AND PULL WIRING BACK TO ABOVE THE ACCESSIBLE CEILING. EXTEND ACTIVE SWITCH WIRING TO NEW SWITCH LOCATION SHOWN ON NEW WORK PLAN.




**CODED NOTES - ELECTRICAL NEW WORK PLAN - LIGHTING**

1. REPLACE TWO SWITCHES AT THIS LOCATION WITH TWO THREE-WAY SWITCHES FOR CONTROL OF LIGHTING AT THIS LOCATION AND AT THE LOCATION DESIGNATED BY CODED NOTE NO. 2. SWITCHES SHALL CONTROL LIGHTING ZONES AS THEY ARE CURRENTLY ZONED (ONE SWITCH CONTROLS FIXTURES WITH DESIGNATION 'a' AND THE OTHER SWITCH CONTROLS FIXTURE WITH DESIGNATION 'b').
2. PROVIDE TWO NEW THREE-WAY SWITCHES AT THIS LOCATION TO CONTROL LIGHTING IN THIS ROOM AS DESCRIBED IN CODED NOTE NO. 1. PROVIDE SINGLE-CHANNEL SURFACE RACEWAY FOR NEW SWITCH AND ASSOCIATED WIRING. WIREMOLD 3000 SERIES OR EQUAL.
3. REPLACE TWO SWITCHES AT THIS LOCATION WITH TWO THREE-WAY SWITCHES FOR CONTROL OF LIGHTING AT THIS LOCATION AND AT THE LOCATION DESIGNATED BY CODED NOTE NO. 4. REVISE SWITCH WIRING IN THIS ROOM SO THAT ONE SWITCH CONTROLS FIXTURES WITH DESIGNATION 'a' AND THE OTHER SWITCH CONTROLS FIXTURE WITH DESIGNATION 'b'.
4. PROVIDE TWO NEW THREE-WAY SWITCHES AT THIS LOCATION TO CONTROL LIGHTING IN THIS ROOM AS DESCRIBED IN CODED NOTE NO. 3. PROVIDE SINGLE-CHANNEL SURFACE RACEWAY FOR NEW SWITCH AND ASSOCIATED WIRING. WIREMOLD 3000 SERIES OR EQUAL.
5. PROVIDE NEW EMERGENCY BATTERY PACK AND CONNECT TO EXISTING CIRCUITING AT THIS LOCATION. EXTEND EXISTING WIRING AS REQUIRED TO ACCOMMODATE NEW LOCATION.
6. PROVIDE NEW EMERGENCY BATTERY PACK AS SHOWN. CIRCUIT BATTERY BACK TO SAME CIRCUIT FEEDING LIGHTING IN THIS ROOM AHEAD OF ANY LOCAL SWITCHING.
7. PROVIDE NEW THREE-WAY SWITCH AT THIS LOCATION AND EXTEND EXISTING SWITCH WIRING TO NEW SWITCH LOCATION. PROVIDE SINGLE-CHANNEL SURFACE RACEWAY FOR NEW SWITCH AND ASSOCIATED WIRING. WIREMOLD 3000 SERIES OR EQUAL.
8. PROVIDE NEW FOUR-WAY SWITCH AT THIS LOCATION AND EXTEND EXISTING SWITCH WIRING TO NEW SWITCH LOCATION. PROVIDE SINGLE-CHANNEL SURFACE RACEWAY FOR NEW SWITCH AND ASSOCIATED WIRING. WIREMOLD 3000 SERIES OR EQUAL.


1 CHEMISTRY DEPARTMENT ELECTRICAL DEMOLITION PLAN - LIGHTING  
1/8" = 1'-0"

2 CHEMISTRY DEPARTMENT NEW WORK PLAN - LIGHTING  
1/8" = 1'-0"



**CODED NOTES - ELECTRICAL DEMO PLAN - POWER & SYSTEMS**

1. UNLESS NOTED OTHERWISE, ALL EXISTING ELECTRICAL DEVICES TO REMAIN, INCLUDING BUT NOT LIMITED TO: RECEPTACLES, RACEWAYS, OUTLET BOXES, CONTACTORS, POWER CONNECTIONS TO EQUIPMENT, FIRE ALARM DEVICES, TELEPHONE/DATA JACKS, AND ALL ASSOCIATED WIRING AND CONDUIT. REFER TO GENERAL NOTE F FOR ADDITIONAL INFORMATION REGARDING RECEPTACLES DESIGNATED AS XRN.
2. REMOVE EXISTING RECEPTACLE MOUNTED IN CASEWORK. UNDER BASE BID, REMOVE EXISTING WIRING AND CONDUIT BACK TO ABOVE CEILING AND LEAVE FOR RECONNECTION TO NEW DEVICES AS SHOWN ON NEW WORK PLAN. EACH RECEPTACLE IS A DEDICATED CIRCUIT. CIRCUITING SHOWN ON NEW WORK PLAN MATCHES EXISTING CIRCUIT NUMBERS. UNDER ALTERNATE BID, REMOVE EXISTING WIRING AND CONDUIT BACK TO PANELBOARD OF ORIGIN. TYPICAL FOR ALL RECEPTACLES SHOWN IN THIS PIECE OF CASEWORK.
3. EXISTING FUME HOOD TO BE REMOVED AND REPLACED WITH NEW BY GC. EC TO DISCONNECT POWER TO EXISTING FUME HOOD AND EXISTING EXHAUST FAN. EXISTING WIRING TO REMAIN FOR RECONNECTION TO NEW EQUIPMENT.
4. UNDER BASE BID, EXISTING SURFACE MOUNTED RACEWAY AND ASSOCIATED RECEPTACLES, WIRING, AND CONDUIT TO REMAIN. UNDER ALTERNATE BID, REPLACE WITH NEW AS DESCRIBED ON NEW WORK PLAN.
5. UNDER ALTERNATE BID, REMOVE ALL EXISTING RECEPTACLES IN THIS ROOM AND REPLACE WITH NEW AS DESCRIBED ON NEW WORK PLAN AND REMOVE ALL ASSOCIATED WIRING BACK TO PANELBOARD OF ORIGIN.
6. UNDER ALTERNATE BID, EXISTING PANELBOARD FEEDING RECEPTACLES WITHIN THIS ROOM TO REMAIN. UNDER ALTERNATE BID, REPLACE EXISTING PANELBOARD INTERIOR AND PORTION OF FEEDER BACK TO ASSOCIATED CONTACTOR AS DESCRIBED ON NEW WORK PLAN.
7. REMOVE EMERGENCY PUSH BUTTON AND ASSOCIATED CONTROL CABLING BACK TO ASSOCIATED CONTACTOR AND REPLACE WITH NEW AS SHOWN ON NEW WORK PLAN.
8. EXISTING STEAM GENERATOR TO BE REMOVED AND REPLACED WITH NEW BY PC. EC TO DISCONNECT POWER. EXISTING DISCONNECT SWITCH AND WIRING TO REMAIN FOR RECONNECTION TO NEW UNIT.
9. EXISTING XRN 150A/SP ASCO 911 REMOTE CONTROL SWITCH (CONTACTOR) MOUNTED IN ENCLOSURE LOCATED ABOVE CEILING. CONTACTOR IS USED TO DISCONNECT POWER TO ADJACENT PANELBOARD UPON ACTIVATION OF ASSOCIATED EMERGENCY PUSH BUTTON. REPLACE EXISTING CONTACTOR WITH NEW AS SHOWN ON NEW WORK PLAN.
10. REMOVE EXISTING POWER POLE IN ITS ENTIRETY. REMOVE ALL BRANCH CIRCUIT WIRING BACK TO SOURCE. REMOVE DATA CABLING TO ABOVE ACCESSIBLE CEILING, COIL, AND LABEL FOR REUSE OR REMOVAL BY OWNER.



**CODED NOTES - ELECTRICAL NEW WORK PLAN - POWER & SYSTEMS**

1. PROVIDE NEW GFCI RECEPTACLES TO REPLACE ALL EXISTING RECEPTACLES IN THIS ROOM AND ASSOCIATED CONTROL WIRING BETWEEN CONTROL STATION, SECOND CONTROL STATION (PUSHBUTTON) LOCATION WITHIN ROOM, AND ASSOCIATED CONTACTOR. PROVIDE ENGRAVED NAMEPLATE AT CONTROL STATION LOCATION.
2. PROVIDE POWER TO RECEPTACLES MOUNTED IN CASEWORK. EC TO INSTALL AND WIRE RECEPTACLE, FURNISH WITH CASEWORK AND PROVIDE FINAL CONNECTION TO EACH DEVICE. UNDER ALTERNATE BID, PROVIDE NEW CIRCUITING AS SHOWN FROM DESIGNATED PANELBOARD. TYPICAL FOR ALL RECEPTACLES SHOWN IN THIS PIECE OF CASEWORK.
3. EXTEND EXISTING CIRCUITING AND PROVIDE FINAL CONNECTION TO NEW FUME HOOD AND EXHAUST FAN. REFER TO DETAIL 3E100 FOR CONNECTION REQUIREMENTS. COORDINATE CONNECTIONS WITH GC AND HC.
4. UNDER ALTERNATE BID, PROVIDE NEW SINGLE-CHANNEL SURFACE-MOUNTED RACEWAY (WIREMOLD 3000 OR EQUAL) AND ASSOCIATED RECEPTACLES. PROVIDE NEW WIRING TO DEVICES FROM DESIGNATED CIRCUIT.
5. UNDER ALTERNATE BID, REPLACE EXISTING PANELBOARD INTERIOR WITH NEW AND REPLACE EXISTING PORTION OF FEEDER FROM ASSOCIATED CONTACTOR TO PANELBOARD (4-4/8" AND 1-4/8" GROUND IN 2" CONDUIT).
6. PROVIDE KEY-OPERATED EMERGENCY POWER AND GAS SHUT-OFF CONTROL STATION, ASCO #17317 AND ASSOCIATED CONTROL WIRING BETWEEN CONTROL STATION, SECOND CONTROL STATION (PUSHBUTTON) LOCATION WITHIN ROOM, AND ASSOCIATED CONTACTOR. PROVIDE ENGRAVED NAMEPLATE AT CONTROL STATION LOCATION.
7. PROVIDE MUSHROOM PUSHBUTTON EMERGENCY POWER AND GAS SHUT-OFF CONTROL STATION, ASCO #17319 AND ASSOCIATED CONTROL WIRING BETWEEN CONTROL STATION, SECOND CONTROL STATION (PUSHBUTTON) LOCATION WITHIN ROOM, AND ASSOCIATED CONTACTOR. PROVIDE ENGRAVED NAMEPLATE AT CONTROL STATION LOCATION.
8. EXISTING REMOTE CONTROL SWITCH (CONTACTOR) MOUNTED IN ENCLOSURE LOCATED ABOVE CEILING TO DISCONNECT POWER TO ADJACENT PANELBOARD UPON ACTIVATION OF ASSOCIATED EMERGENCY PUSH BUTTONS DESCRIBED IN CODED NOTES 6 AND 7. PROVIDE ALL CONTROL WIRING AS REQUIRED FOR COMPLETE OPERATION.
9. LOCATION OF SERVICE CHASE. UTILIZE SERVICE CHASE TO EXTEND POWER FROM ABOVE ACCESSIBLE CEILING INTO CASEWORK AND TO RECEPTACLE LOCATIONS.
10. PROVIDE POWER TO RECEPTACLES AND RACEWAY FOR FUTURE DATA JACKS MOUNTED IN CASEWORK. EC TO INSTALL AND WIRE RECEPTACLE. FURNISH WITH CASEWORK (ONE DUPLEX RECEPTACLE IN ONE GANG OF COUNTERMOUNTED DOORHOUSE). UNDER BASE BID, EXTEND EXISTING CIRCUITING FROM ABOVE CEILING INTO CASEWORK AND PROVIDE FINAL CONNECTION TO EACH DEVICE. UNDER ALTERNATE BID, PROVIDE NEW CIRCUITING AS SHOWN FROM DESIGNATED PANELBOARD. PROVIDE FLEXIBLE NON-METALLIC CONDUIT FROM ABOVE THE ACCESSIBLE CEILING TO SECOND GANG AT EACH DOORHOUSE LOCATION FOR DATA CABLING BY OTHERS. PROVIDE PULL WIRE IN CONDUIT. TYPICAL FOR ALL RECEPTACLES SHOWN IN THIS PIECE OF CASEWORK.
11. CIRCUIT RECEPTACLES TO SPARE CIRCUIT BREAKER IN DESIGNATED PANEL.
12. EXTEND EXISTING CIRCUITING AND PROVIDE FINAL CONNECTION TO NEW STEAM GENERATOR. REFER TO DETAIL 4E100 FOR CONNECTION REQUIREMENTS. COORDINATE CONNECTION REQUIREMENTS WITH PC.
13. EXISTING PANEL 'CH' IS A 225A, 120/208V, 3PH, 4W MLO PANEL WITH (4) 20A/1P CIRCUIT BREAKERS.
14. EXISTING PANEL 'C' CONSISTS OF TWO 225A, 120/208V, 3PH, 4W MLO PANELS. SECTION ONE HAS (1) 20A/1P CIRCUIT BREAKER, (1) 20A/1P GFCI BREAKER, AND (2) 20A/1P CIRCUIT BREAKERS. SECTION TWO HAS (2) 20A/1P CIRCUIT BREAKERS.
15. EXISTING PANEL 'C2' CONSISTS OF TWO 225A, 120/208V, 3PH, 4W MLO PANELS. SECTION ONE HAS (3) 20A/1P CIRCUIT BREAKERS. SECTION TWO HAS (1) 20A/2P CIRCUIT BREAKER AND (18) 20A/1P CIRCUIT BREAKERS.
16. PROVIDE POWER CONNECTION TO GLASSWARE WASHER. ROUTE 2-412 AND 1-412 GROUND IN 3/4" CONDUIT TO SPARE CIRCUIT BREAKER IN DESIGNATED PANELBOARD. COORDINATE CONNECTION REQUIREMENTS WITH MANUFACTURER'S WRITTEN RECOMMENDATIONS AND PROVIDE COMPLETE CONNECTION AS REQUIRED.
17. PROVIDE GFCI RECEPTACLE MOUNTED AT 48" AFF FOR NEW ICEMAKER.

3 CHEMISTRY DEPARTMENT ELECTRICAL DEMOLITION PLAN - POWER & SYSTEMS  
1/8" = 1'-0"

4 CHEMISTRY DEPARTMENT NEW WORK PLAN - POWER & SYSTEMS  
1/8" = 1'-0"

**GENERAL NOTES - SHEET E101**

- A. WHERE EXISTING DEVICES ARE REMOVED FROM EXISTING-TO-REMAIN WALLS, THE ELECTRICAL CONTRACTOR SHALL DO ONE OF THE FOLLOWING: IN DRYWALL WALLS, PATCH WALL TO MATCH EXISTING; IN BRICK/MASONRY WALLS, REPAIR/REPLACE WITH CASEWORK; IN STAINLESS STEEL COUPLER/OUTLET BOX, PAINT COVER TO MATCH ADJACENT WALL.
- B. WHERE BRICK/MASONRY WALLS ARE REQUIRED BY GENERAL AND/OR CODED NOTES, PROVIDE PLATES THAT MEET THE FOLLOWING REQUIREMENTS: FABRICATED FROM FLAT STAINLESS STEEL WITH BEVELLED EDGES AND A FINE BRUSHED FINISH TO MATCH RECEPTACLE FACEPLATES. CONTRACTOR SHALL FIELD VERIFY ALL LOCATIONS.
- C. COORDINATE DISCONNECTION AND REMOVAL OF ALL EQUIPMENT AND DEVICES WITH PHASING SCHEDULE.
- D. CIRCUIT ALL EMERGENCY BATTERY UNITS USED AS EMERGENCY LIGHT FIXTURES AHEAD OF ANY LOCAL SWITCHING/CONTROLS.
- E. PROVIDE RECEIPT ON COVERPLATE OF ALL ELECTRICAL DEVICE FACEPLATES INDICATING PANELBOARD OF ORIGIN AND CIRCUIT NUMBER.
- F. WHERE RECEPTACLES ARE NOTED AS XRN:
  - a. UNDER BASE BID, REMOVE EXISTING RECEPTACLE AND REPLACE WITH NEW GFCI RECEPTACLE IN EXISTING FACEPLATE. REMOVE NEW DEVICE TO EXISTING BRANCH CIRCUIT WIRING. PROVIDE NEW FACEPLATE.
  - b. UNDER ALTERNATE BID, REPLACE EXISTING RECEPTACLE AND ASSOCIATED BRANCH CIRCUIT WIRING BACK TO PANELBOARD. REPLACE WITH NEW GFCI TYPE RECEPTACLE IN EXISTING BACKBOX AND PROVIDE NEW BRANCH CIRCUIT WIRING (2-412 AND 1-412 GROUND) IN EXISTING CONDUIT. PROVIDE NEW FACEPLATE.
- G. ALL NEW DUPLEX RECEPTACLES SHOWN ABOVE COUNTERTOPS SHALL BE GFCI TYPE.
- H. UNLESS NOTED OTHERWISE, INSTALL NEW DEVICES AND CABLING CONCEALED IN WALLS. IN AREAS OF RENOVATION, WHERE POSSIBLE, UTILIZE EXISTING JOINT OR WALL CAVITY AS RACEWAY. WHERE EXISTING WALL CANNOT BE FISHED, PROVIDE SURFACE MOUNTED BACKBOX AND SURFACE METAL RACEWAY. WHERE RACEWAY FEEDS ONLY ONE TYPE OF CABLING, PROVIDE SINGLE-CHANNEL RACEWAY. WIREMOLD 3000 SERIES. IN ORDER TO MAINTAIN A NEAT INSTALLATION, COORDINATE EXACT LOCATIONS OF ALL SURFACE RACEWAY INSTALLATIONS WITH ARCHITECT PRIOR TO ROUGH-IN.